



UNIVERSITEIT•STELLENBOSCH•UNIVERSITY
jou kennisvennoot • your knowledge partner

The `usthesis` Class and Style*

Danie Els[†]

e-mail: `dnjels@sun.ac.za`

DEPARTMENT OF MECHANICAL ENGINEERING,
UNIVERSITY OF STELLENBOSCH,
PRIVATE BAG X1, MATIELAND, 7602.

2006/09/14

Abstract

The `usthesis` class/style files are provided to typeset reports, theses and dissertations that conform to the requirements of the Engineering Faculty of the University of Stellenbosch, South Africa.

The class file `usthesis.cls` is based on the standard L^AT_EX `book` class, while `usthesis.sty` is a style file to be loaded on top of the very powerful `memoir` class. Both options give identical output, but the benefit of the using `memoir` is that it has many additional command and environments for formatting and processing of a document.

`Usthesis` is primarily concerned with the formatting of the front matter such as the title page, abstract, etc. It also works together with the `babel` package to provide language options to typeset documents in Afrikaans or in English.

*This class has version number v2.2a, last revised 2006/09/14.

[†]Any help with proofreading this document will be appreciated.

Contents

1	User Interface	4
1.1	usthesis class and style files	4
1.1.1	Loading the <code>usthesis</code> packages	4
1.1.2	The <code>usthesis</code> options:	4
1.1.3	L ^A T _E X class options:	6
1.1.4	Global package options:	7
1.2	Required Packages	7
1.2.1	Language setup	7
1.2.2	Input font encoding	9
1.2.3	Output font encoding	9
1.2.4	Font selection	9
1.2.5	Mathematics	10
1.2.6	Graphics and Color	10
1.2.7	Line spacing	11
1.2.8	Paragraph indent and spacing	11
1.3	Useful packages	11
1.3.1	SI units and numbers	11
1.3.2	Tables and arrays	12
1.3.3	Hyper links	12
2	Front matter	13
2.1	Title page	13
2.2	Custom title page	15
2.3	Copyright page	16
2.4	Declaration page	16
2.5	Abstract	16
2.6	Acknowledgements, Dedications, etc.	17
3	Back Matter	17
3.1	Bibliography/List of References	17
4	Implementation: <code>usthesis</code>	19
4.1	Identification	19
4.2	Options	19
4.2.1	Language options	19
4.2.2	Thesis type options	24
4.2.3	Page layout options	25
4.2.4	Process package options	26
4.3	External packages	26
4.4	Temporaries	27
4.5	Page layout	27
4.5.1	A5 type block area	28
4.5.2	Golden section type block area	28
4.6	Utility commands	29
4.7	Front pages	30
4.7.1	Title page	30
4.7.2	Copyright page	33
4.7.3	Declaration page	34

4.7.4	Abstract page	34
4.7.5	Table of contents	35
4.7.6	List of figures	35
4.7.7	List of tables	36
4.8	Back matter	36
4.8.1	Bibliography	36
4.8.2	Index	37
4.9	Page markup	38
4.9.1	Headers and footers	38
4.9.2	Chapter and section headings	40
4.9.3	Floats and float pages	41
4.9.4	Captions	42

1 User Interface

1.1 `usthesis` class and style files

Two style files are provided to typeset theses of the University of Stellenbosch. The class file `usthesis.cls` is based on the standard L^AT_EX `book` class, while `usthesis.sty` is a style file to be loaded on top of the very powerful `memoir` class. Both options give identical output, but the benefit of the using `memoir` is that it has many additional command and environments for formatting and processing of a document.

1.1.1 Loading the `usthesis` packages

The `usthesis.cls` class is loaded in the document preamble with

```
\documentclass[12pt,oneside,openany,a4paper, %... Layout
              afrikaans,UKenglish,         %... Global language drivers
              masters-t, goldenblock        %... Thesis options
]{usthesis}
```

or `usthesis.sty` together with the `memoir` class

```
\documentclass[12pt,oneside,openany,a4paper, %... Layout
              afrikaans,UKenglish,         %... Global language drivers
]{memoir}
\usepackage[masters-t, goldenblock]{usthesis} %... Thesis options

% --- If hyperref is loaded together with memoir ---
\iftrue
  \usepackage[⟨hyperref options⟩]{hyperref} %... Hyperlinks
  \usepackage{memhfixc}                   %... Memoir fix
\else
  \usepackage{nohyperref}                  %... Disable hyperlinks
\fi
\hypersetup{⟨hyperref setup options⟩}
```

Please note when the `memoir` is used together with `hyperref` the the `memhfixc` patch must be loaded afterwards.

1.1.2 The `usthesis` options:

Document type options: This options for the `usthesis` class/style are for specific formatting of the title and abstract pages of the different document types.

report: Final year project reports, etc.

masters-a: An assignment masters degree.

masters-t: A thesis masters degree.

PhD: A PhD dissertation handed in for examination.

PhDfinal: A PhD dissertation handed in for publication after acceptance.

Type block sizes: The ISO A4 paper size (297,3 mm \times 210,2 mm) is not ideally suited for typesetting off books. The *A5 type block* (fig 1) and the *golden section type block* (fig 2) are layouts designed by the great typographer Jan Tschichold which adheres to the classic typographic principals. A 12 pt font size is recommended for most fonts.

The following options are provided as part of the `usthesis` class/style options:

`a5block`: ISO A4 paper with A5 type block

`goldenblock`: ISO A4 paper with golden ration type block, .

`stdblock`: Standard L^AT_EX type block [default].




Figure 1: ISO A4 paper with A5 type block (`A5block`)




Figure 2: ISO A4 paper with golden ration type block (`goldenblock`)

Table 1: Page layout parameters

	A5 type block (a5block)		Golden section type block (goldenblock)	
Page width	W	$= 210,2 \text{ mm}$	W	$= 210,2 \text{ mm}$
Page height	$H = \sqrt{2} W$	$= 297,3 \text{ mm}$	$H = \sqrt{2} W$	$= 297,3 \text{ mm}$
Block width	$w = H/2$	$= 148,7 \text{ mm}$	$w = 2W/3$	$= 140,1 \text{ mm}$
Block height	$h = W$	$= 210,2 \text{ mm}$	$h = H - W/3$	$= 227,2 \text{ mm}$
Spine margin	$s = 3(W - w)/8$	$= 23,1 \text{ mm}$	$s = 3W/24$	$= 26,3 \text{ mm}$
Fore-edge margin	$e = 5(W - w)/8$	$= 38,5 \text{ mm}$	$e = 5W/24$	$= 43,8 \text{ mm}$
Top margin	$t = 3(H - h)/8$	$= 32,7 \text{ mm}$	$t = 3W/24$	$= 26,3 \text{ mm}$
Foot margin	$f = 5(H - h)/8$	$= 54,4 \text{ mm}$	$f = 5W/24$	$= 43,8 \text{ mm}$

The user can set up custom page layouts if needed. The setup depends on the class file used. The following example is for a page with 25 mm margins all around.

1. memoir.cls with usthesis.sty

```
\documentclass[a4paper,<options>]{memoir}
\usepackage[<options>]{usthesis}
\setlrmarginsandblock{25mm}{25mm}{*} % Left/Right margins
\setulmarginsandblock{25mm}{25mm}{*} % Upper/Lower margins
\checkandfixthelayout
\setlength{\headwidth}{\textwidth}
```

2. usthesis.cls

```
\documentclass[a4paper,<options>]{usthesis}
\usepackage[
  hmargin={25mm,25mm},
  vmargin={25mm,25mm}
]{geometry}
```

1.1.3 L^AT_EX class options:

The gray `boxes` are the L^AT_EX default options, while `boxed` options are the preferred options of usthesis package.

`10pt`, `11pt`, `12pt`: Sets the size of the main font in the document. The preferred font size depends very much on the font type. For Computer Modern (the default L^AT_EX font) is 11 or 12 points the most legible option on an A4 paper size.

`a4paper`, `a5paper`, `b5paper`, `letterpaper`, `executivepaper`, `legalpaper`: Defines the paper size. In South Africa is the ISO A4 paper size the standard.

`fleqn`: Typesets displayed formulae left-aligned instead of centred. This option is a matter of personal taste (but compulsory for Prof. Detlev Kröger's students).

leqno: Places the numbering of formulae on the left hand side instead of the right. This is the traditional layout of the American Mathematical Society, but is not used for Engineering theses.

onecolumn, **twocolumn**: Instructs L^AT_EX to typeset the document in one column or two columns. The University of Stellenbosch Engineering theses are traditionally single column documents.

twoside, **oneside**: Specifies whether double or single sided output should be generated. Note that this option concerns the style of the document only. The option **twoside** does not tell the printer you use that it should actually make a two-sided printout. If a printer with double sided printing capability is available, then this option can be used.

openright, **openany**: Makes chapters begin either only on right hand pages or on the next page available. Selection of **openright** depends on the selection of the **twoside** option.

1.1.4 Global package options:

Global options for packages and drivers can be loaded together with the class options. The most important options are the display drivers for **color**, **graphicx** and **hyperref** as well as the language options for **babel**, **varioref**, etc.

The **display drivers** are normally loaded by the L^AT_EX config system defaults.

The **global language options** for **babel** can be set with:

```
\documentclass[⟨options⟩, afrikaans, UKenglish]{usthesis}
\usepackage{babel}
\usepackage{varioref}
```

1.2 Required Packages

1.2.1 Language setup

L^AT_EX provides for a variety of languages. It set up hyphenation patterns and define language specific output such as chapter names, etc. The default language is American style English, while the South African English is the United Kingdom style.

Language options must be loaded with the **babel** package. The last language declared is the default document language.

```
\usepackage[afrikaans, UKenglish]{babel} → UK English default.
\usepackage[UKenglish, afrikaans]{babel} → Afrikaans default.
```

or preferably with global options

```
\documentclass[⟨options⟩, afrikaans, UKenglish]{usthesis}
\usepackage{babel}
```

Languages can be made active with the `\selectlanguage{<lang-name>}` command from **babel**. In the **usthesis** class, a command

`\AorE` `\AorE{<Afr-tekst>}{<Eng-text>}`

is provided that types one of the two arguments, depending on whether **afrikaans** is the active language or not. Environments for changing the language options locally are also provided in **usthesis** (if languages are installed with **babel**).

Afr	<code>\begin{Afr}</code>	<code>\begin{Eng}</code>
	<i>Afr-tekst ...</i>	<i>Eng-text ...</i>
Eng	<code>\end{Afr}</code>	<code>\end{Eng}</code>

Table 2: Definitions from **babel** loaded with the **afrikaans** option.

"e	The character ë which hyphenates as -e. Implemented for the letters ä, ë, ï, ö and ü.
"	Disable ligatures (ff, fi, ffi, etc.) at this position but allows a hyphen, e.g.: The word ‘stoffer’ looks better as ‘stoffilter’. It is then hyphenated as ‘stof-filter’
"-	An explicit hyphen sign, allowing hyphenation in the rest of the word.
"~	To produce a hyphen character without the following discretionary break after it, e.g.: ‘x-straal’.
" "	To produce an invisible breakpoint.
"‘	Lowered double left quotes, e.g.: „lowered” versus “normal”.
"’	Normal double right quotes.
"/	Enable hyphenation in two words, written together but separated by a slash, for example ‘uitdrukking/opmerking’.
\-	A redefinition of the standard discretionary hyphen, \-. The new version indicates an extra hyphenation position, while allowing other hyphenation positions to be generated automatically.

With the **afrikaans** option of **babel** the character " is made active. In table 2 an overview is given of its purpose. One of the reasons for this is that in the Afrikaans language a word with a dieresis can be hyphenated just before the letter with the umlaut, but the dieresis has to disappear if the word is broken between the previous letter and the accented letter, for example ‘geëerd’ becomes ‘ge-eerd’. It is extremely important that the commands "a, "e, ..., are used in Afrikaans documents, and not \ "e, etc., and neither the direct input of ë with **Alt+137** (if **latin1** input encoding is selected).

The **afrikaans** option sometimes has problems with the hyphenation of the very long Afrikaans words, but it does a fairly good job, e.g.:

`\showhyphens{appelkooskonfytblik}` → ap-pel-koos-kon-fyt-blik

The simplest way to correct a wrongly hyphenated word is to include the discretionary hyphen command `\-` in the word: e.g.: `kom\-buis\-kas`.

Words that incorrectly hyphenated and appear frequently within the document can be put into a list of exceptions in the preamble of the document:

```
\hyphenation{Kom-buis-kas ...}
```

It is also important to note that words that contain "e, etc. must be hyphenated by hand when they are near linebreaks, for example: `koëffisiëntematriks`

```
ko"ef\-fisi"en\-te\-mat\-riks
```

1.2.2 Input font encoding

In Afrikaans there are many words containing characters such as é, ô, à, ï, etc. These characters can be included directly in the input text file, except ä, ë, ï, ö and ü, which need to be inserted as "a, ..., for proper hyphenation (see previous section). As an example by typing `Alt+136`, you obtain `ê`. If the Western European input encoding (latin1) is loaded, L^AT_EX will recognize these characters.

```
\usepackage[latin1]{inputenc}
```

1.2.3 Output font encoding

The classic T_EX Computer Modern fonts contain only 126 characters (7-bit) per font set (OT1 encoding). It does not contain glyphs for characters such as `ê`. These characters are formed by two characters that are overprinted (`^+e`). The result is that Afrikaans words such as "*koëffisiëntematriks*," are not hyphenated automatically. The solution is to use the T1 encoding scheme with 256 character (8-bit) font sets. Postscript Type 1 and TrueType fonts can be configured, with the aid of T_EX's virtual font mechanism, to be available for L^AT_EX. Font handling can be switched to T1 encoding (if you have the Postscript or the re-encoded TrueType fonts).

```
\usepackage[T1]{fontenc}
```

1.2.4 Font selection

To obtain a PDF e-document of your thesis you need to use Postscript fonts (and T1 encoding for Afrikaans). There are many free Postscript text fonts available in the T_EX distributions, but Postscript fonts with a full set of mathematical symbols are very scarce. The freely available ones are:

Computer Modern (CM-super): Newer L^AT_EX installations contain this classic T_EX font in Type 1 format. This font set is loaded by default if T1 encoding is specified without any other font loaded. This document is set in Computer Modern.

Palatino: This beautiful font can be loaded with the `mathpazo` package. Palatino is one of the standard Postscript fonts on every Postscript printer.

Make sure that the `fpl` fonts are loaded. They provide true small caps and old style figures for the Palatino fonts.

Times Roman: This font is loaded with the mathptmx package. It contains no bold math characters or true small caps. Please do not use this font for theses, because it was designed for narrow newspaper columns resulting in very narrow characters. It is just not appropriate for single column theses.

Utopia: This font is loaded with the fourier package. It contains no true small caps. This font is very good on low resolution output devices.

CMbright: This is a sans serif font and is part of the CM-super font set. It can be loaded with the cmbright package. You need the hfbright fonts installed for the math symbols. A document with a sans serif font, such as CMbright, must be set ragged right. Use the `\RaggedRight` command of the ragged2e package.

Euler: This is a math font only and can be used with fonts such as Charter that do not have math characters. It is loaded with the eulervm package.

An example of a typical setup for an Afrikaans report with mathematics is:

```
\documentclass[report,                %... Document type
               12pt,oneside,openany,a4paper,%... Layout
               a5block,                %... Typeblock
               UKenglish,afrikaans,    %... Global language drivers
               ]{usthesis}

\usepackage{babel}%..... Language setup
\usepackage[latin1]{inputenc}% Recognizes ê, ë, etc
\usepackage{amsmath}%..... Advanced maths (before fonts)
\usepackage[T1]{fontenc}%..... Type 1 output fonts for proper hyphenation
\usepackage{textcomp}%..... Additional text characters
\usepackage{fourier}%..... Utopia (if you want a different font)
\usepackage{bm}%..... Bold math characters (after fonts)
```

1.2.5 Mathematics

Normal L^AT_EX contains many math typesetting commands and environments, but for serious mathematical typesetting you need to load the American Mathematical Society ($\mathcal{A}\mathcal{M}\mathcal{S}$) math packages. The $\mathcal{A}\mathcal{M}\mathcal{S}$ packages also include additional math symbols, but load it only if really necessary, because they are very big.

```
\usepackage{amsmath}
\usepackage{amssymb}% only if necessary
```

Bold math symbols can be obtained with the $\mathcal{A}\mathcal{M}\mathcal{S}$ command `\boldsymbol` or with the more advanced `\bm` command from the `bm` package.

1.2.6 Graphics and Color

The `graphicx` package is needed by the `usthesis` package to format the title page and must be loaded in the document preamble. The `color` package is optional, but very useful.

```
\usepackage[<options>]{graphicx}
\usepackage[<options>]{color}
```

If you need display drivers (such as `dvips`, `pdftex`, etc.) different from the default options, is it important that they are passed on to all the packages as a global option. With the MiKTeX this is achieved with the standard configuration file.

1.2.7 Line spacing

The guidelines for University of Stellenbosch theses dictates that either single, one-half or double line spacing be used. Line spacing can be obtained with the `setspace` packages. With this packages, footnotes and captions are still single spaced, while no additional vertical spacing is added around display math or in lists.

```
\documentclass[12pt,oneside,openany,a4paper,%... Layout
               afrikaans,UKenglish,%..... Global language drivers
               ]{memoir}
\usepackage[masters-a,a5block]{usthesis}%..... Document type
:
\usepackage[onehalfspacing]{setspace}%..... Line spacing
:
\begin{document}
  \frontmatter
  \begin{singlespace}
    \TitlePage%..... Single spaced title page
  \end{singlespace}
  :
```

1.2.8 Paragraph indent and spacing

The conventional way of typesetting running text has no separation between paragraphs, and the first line of each paragraph in a block of text indented.

It is sometimes required that paragraphs are separated with a blank line and without any first line indent. This can be obtained with the `parskip` package.

```
\usepackage{parskip}
```

Please note that this is not recommended for theses containing large amounts of mathematics, because it is difficult, if not impossible, to see where a new paragraph starts between equations.

1.3 Useful packages

The following are a number of packages that are very useful when writing a thesis.

1.3.1 SI units and numbers

Sistyle: This package is essential for the proper typesetting of SI units and numbers. It has an option for South African requirements. Read the documentation for the proper typesetting of units and numbers.

numprint: This packages typeset numbers and decimal columns in tables.

1.3.2 Tables and arrays

array: An extended implementation of the array and tabular environments which implements options to format columns.

longtable: Gives non-floating multi-page tables. It includes continuation headers.

dcolum: The package provides a system for defining columns of entries in an array or a table which are to be aligned on a “decimal point”.

dcolum: It modifies the width of certain columns to obtain a table with required width.

booktabs: The package provides some additional commands to enhance the quality of tables in L^AT_EX. Guidelines are given as to what constitutes a good table. The documentation gives a very good discussion on the design of publication quality tables.

1.3.3 Hyper links

hyperref: It extends the functionality of all the L^AT_EX cross-referencing commands (including the table of contents, bibliographies etc) to produce hypertext links; it also provides new commands to allow the user to write ad hoc hypertext links, including those to external documents and URLs.

url A form of **that** allows line breaks at certain characters or combinations of characters, accepts reconfiguration, and can usually be used in the argument to another command. It is intended for email addresses, hypertext links, directories/paths, etc., which normally have no spaces.

It is implemented by **hyperref**.

A typical setup for hyper links (at the end of the preamble) is:

```
\iftrue
  \usepackage{hyperref}%..... Hyperlinks & backreferences
  %\usepackage{memhfixc} %..... Memoir fix
  \hypersetup{plainpages = false,
    breaklinks=true,
    a4paper=true,
    linktocpage,
    linkbordercolor = {0.8 0.8 0.8},
    urlbordercolor = {0.8 0.8 0.8},
    menubordercolor = {0.8 0.8 0.8},
    filebordercolor = {0.8 0.8 0.8},
    runbordercolor = {0.8 0.8 0.8},
    citebordercolor = {0.8 0.8 0.8},
    pagebordercolor = {0.8 0.8 0.8},
    pdfauthor={Danie Els},
    pdfkeywords={}}
\else
  \usepackage{nohyperref}%..... Disable hyperlinks
  \usepackage{url}
\fi
```

2 Front matter

2.1 Title page

The title page is inserted on the first page of a document with the command

`\TitlePage` `\TitlePage`

Depending on the selected options, the following commands are used to set the contents of the title page:

Address

`\address` `\address{\full address}`

The address must be included in Afrikaans and English for Masters and PhD documents.

```
\address{\AorE{
  Departement Meganiese Ingenieurswese,\
  Universiteit van Stellenbosch,\
  Privaatsak X1, 7602 Matieland, Suid Afrika.
}{
  Department of Mechanical Engineering,\
  University of Stellenbosch,\
  Private Bag X1, 7602 Matieland, South Africa.
}}
```

Author

`\author{\short name}{\full names}`

Provides the author name not only for the title page, but for various other places in the document.

```
\author{J.F.\ Els}{Jacobus Frederik Els}
```

Date

`\date{\month}{\year}`

The date when the document is handed in. The arguments must be numerical, e.g.:

```
\date{10}{2003} → October 2003
```

Degree/Subject

`\degree` `\degree{\abbr}{\full name}` or `\subject{\abbr}{\full name}`

The degree or subject names. Please refer to the yearbook for the *correct* names. The degree names must be available in Afrikaans and English.

```

\degree{\AorE{MScIng (Meg)}{MScEng (Mech)}}
      {\AorE{Magister in die Natuurwetenskappe in Meganiese Ingenieurswese}
        {Master of Science in Mechanical Engineering}}
or
\subject{MP 487}{Meganiese Projek 487}

```

Description

\ReportDescript
\ThesisDescript

\ReportDescript{<text>} \ThesisDescript{<text>}
--

Set the description for reports.

```
\ReportDescript{Finale Verslag}
```

There is a similar command for theses and dissertations, \ThesisDescript, but its contents is predefined. The for a master thesis it can be customized as

```

\ThesisDescript{\ThesisType\ presented in partial fulfilment
  of the requirements for the degree of\par
  \vspace{1em}
  {\bfseries Master of Science in Mechanical Engineering\par}
  \vspace{1em}
  at the \USName}

```

If needed the thesis type can be changed with the (predefined) command \ThesisType.

Supervisor/Studyleader/Promotor

\studyleader
\supervisor
\promotor

\supervisor[<align>]{<name>} or \supervisor{<name> \and <name>} \studyleader[<align>]{<name>} or \studyleader{<name> \and <name>} \promotor[<align>]{<name>} or \promotor{<name> \and <name>}

The \studyleader, \supervisor and \promotor commands are synonyms and the output depends on the thesis type. The commands also have a starred (*) form that stack the names of multiple supervisors. The \and has an optional argument, e.g.: \and[1ex], for spacing in a stacked environment.

```
\supervisor{Mnr.\ D.N.J.\ Els} → Supervisor: Mnr. D.N.J. Els
```

or

```

\supervisor{Mnr.\ D.\ Els
  \and
  Dr.\ J.\ Smith} →
Supervisors:
Mnr. D. Els   Dr. J. Smith

```

or

```

\supervisor*{Mnr.\ D.\ Els
  \and[0ex]
  Dr.\ J.\ Smith} →
Supervisors:
Mnr. D. Els
Dr. J. Smith

```

or for PhD and PhDfinal options


```

\vfll
{\LARGE\noindent Seakeeping control of HYSUCATs \par}
\vspace{2em}
{\large\indent by \par}
\vspace{2em}
{\Large\noindent Giovanni Sergio Milandri \par}%
\vfll\noindent
\begin{minipage}{.9\textwidth} \large\slshape\raggedright
  Thesis presented in partial fulfilment of the requirements for the degree of
  Master of Science in Mechanical Engineering at the University of Stellenbosch
\end{minipage}
\vfll
{\normalfont\noindent
  Department of Mechanical Engineering\ \ University of Stellenbosch\ \
  Private Bag X1, 7602 Matieland, South Africa \par}
\vfll
{\normalsize\noindent Supervisors:\ \ [1.5ex]
\begin{tabular}{@{}ll@{}}
  Prof J.L. van Niekerk & Dr G. Migeotte \ [1.5ex]
  Dept of Mechanical Engineering & Unistel Technologies (Pty) Ltd\ \
  University of Stellenbosch & University of Stellenbosch
\end{tabular}\par}
\vspace{2em}
{\large\noindent April 2006\par}%
\clearpage
%-----

```

2.3 Copyright page

If you need a copyright page for a report, it must be inserted directly after the title page. The default copyright holder is the University of Stellenbosch.

`\CopyrightPage`

<code>\CopyrightPage</code> <code>\CopyrightPage[<i><copyright holder></i>]</code>

2.4 Declaration page

Every thesis and dissertation *must* include a declaration page.

`\DeclarationPage`

<code>\DeclarationPage</code>

The command set the required text in the default language.

2.5 Abstract

An `abstract` environment is provided that prints a page containing all the thesis information. The layout of an abstract for a report differs from that of a thesis or a dissertation. It is also important to note that theses and dissertations require an English and an Afrikaans abstract.

abstract	<code>\begin{abstract}</code> Text in default language ... <code>\end{abstract}</code>	<code>\begin{abstract}[\langle language \rangle]</code> Text in $\langle language \rangle$... <code>\end{abstract}</code>

If the traditional abstract page is preferred, then use a normal chapter

```
\chapter{Abstract}
This thesis ...
```

2.6 Acknowledgements, Dedications, etc.

Acknowledgements, etc. can be include in the front matter of a document after a `\chapter` command, e.g.:

```
\chapter{Acknowledgements}
I would like to express my sincere gratitude ...
```

3 Back Matter

3.1 Bibliography/List of References

The `USbib` package is provided to format bibliographies for theses and dissertations of the University of Stellenbosch. The package is language sensitive and provides the correct output for both Afrikaans and English theses.

Please note the difference between a bibliography and a List of references:

Bibliography: The list of all the citations in numerical order of citation, e.g.:

1. Rhodes, M. *Introduction to Particle Technology*. Wiley, New York (1998).
2. Cleary, P.W. The filling of dragline buckets. *Mathematical Engineering in Industry*, vol. 7, no. 1 (1998), pp. 1–24.

List of References: For author-year citations, all the citations sorted in alphabetic order, e.g.:

Cleary, P.W. (1998). The filling of dragline buckets. *Mathematical Engineering in Industry*, vol. 7, no. 1, pp. 1–24.

Rhodes, M. (1998). *Introduction to Particle Technology*. Wiley, New York.

The default name in the `USthesis` package is “Bibliography”. To change this to “List of References” (for a thesis), we have to overrule the `babel` setup. Make the following declarations

```
\documentclass[12pt,oneside,openany,a4paper,%... Layout
               afrikaans,UKenglish,%..... Global language drivers
               ]{memoir}

\usepackage[masters-t,a5block]{usthesis}%..... Document type
\usepackage{babel}%..... Language setup
:
\usepackage{usbib}%..... Bibliography
\bibliographystyle{usmeg-a}%..... Author-year style
\addto{\captionsafrikaans}{\renewcommand{\bibname}{Lys van Verwysings}}
\addto{\captionsUKenglish}{\renewcommand{\bibname}{List of References}}
```

Back references (referring to the pages or sections of citations) can be included with the `backref` package. The `backref` package loaded as part of `hyperref` or on its own.:

```
\iftrue
  \usepackage[backref=page]{hyperref}%..... Hyperlinks & backreferences
\else
  \usepackage{nohyperref}%..... Disable hyperlinks
  \usepackage[pageref]{backref}%..... Citation backreferences
\fi
\renewcommand*{\backref}[1]{%
\renewcommand*{\backrefalt}[4]{%..... Back reference format
  \ifcase #1 %
    % Not cited.
  \or
    (Cited on page~#2.)%
  \else
    (Cited on pages~#2.)
  \fi}
```

An example is:

Rhodes, M. (1998). *Introduction to Particle Technology*. Wiley,
New York. (Cited on pages 13 and 15.)

4 Implementation: usthesis

The following modules are used in the implementation to direct docstrip in generating the external files:

`cls` produce the document class `usthesis.cls` based on `book`.
`mem` produce the document style `usthesis.sty` for use with `memoir`.

4.1 Identification

```

1 <{*cls | mem>
2 \NeedsTeXFormat{LaTeX2e}[1999/12/01]
3 <{*cls>
4 \def\US@basetype{book}
5 \ProvidesClass{usthesis}[\USfiledate\space
6                               \USfileversion\space
7                               Stellenbosh Thesis class (DNJ ELS)]
8 </cls>
9 <{*mem>
10 \ProvidesPackage{usthesis}[\USfiledate\space
11                               \USfileversion\space
12                               Stellenbosh Thesis class for use with Memoir (DNJ ELS)]
13 \@ifclassloaded{memoir}%
14   {\PackageInfo{usthesis}{Stellenbosch thesis style for MEMOIR class}}%
15   {\PackageError{usthesis}{You must use the Memoir class}{}}
16 </mem>

```

4.2 Options

4.2.1 Language options

Utility commands:

Utility commands and environments to make local language changes.

`\US@AFRstr` String in the right catcode for tests against `\language`.

```
17 \edef\US@AFRstr{\string afrikaans}
```

`\AorE` Command `\AorE{<Afr>}{<Eng>}` to type text depending on the active language.

```
18 \newcommand{\AorE}[2]{%
19   \ifx\US@AFRstr\language #1\else #2\fi}
```

`Afr` Makes an Afrikaans environment inside an English document.

```
20 \newenvironment{Afr}%
21   {\ifx\language\US@AFRstr\relax\else
22     \selectlanguage{afrikaans}%
23     \fi}%
24   {}
```

`\US@ENGstr` Make provisions for all the different types of English. The command is reset within the options.

```
25 \newcommand*\US@ENGstr{}
26 \let\US@ENGstr=\relax
```

Eng Makes an English environment inside an Afrikaans document.

```

27 \newenvironment{Eng}%
28     {\ifx\relax\US@ENGstr\relax\else
29         \ifx\language\US@ENGstr\relax\else
30             \edef\US@tempa{\noexpand\selectlanguage{\US@ENGstr}}%
31             \US@tempa
32         \fi
33     \fi}%
34     {}

```

Maker commands:

Commands of which the contents are defined later.

Degree or subject

```

35 \newcommand\US@degree{%
36 \cls) \ClassWarning{usthesis}{No degree or subject supplied}%
37 \mem) \PackageWarning{usthesis}{No degree or subject supplied}%
38 \textfb{[No degree!]}
39 \newcommand\US@degreeelong{%
40 \cls) \ClassWarning{usthesis}{No degree or subject supplied}%
41 \mem) \PackageWarning{usthesis}{No degree or subject supplied}%
42 \textfb{[No degree!]}

```

Language options:

Declare all the language specific text in separate macros, enabling language changes with the babel package commands.

University name

Afrikaans and English code:

```

43 \newcommand\USNameAFR{Universiteit van Stellenbosch}
44 \newcommand\USNameENG{University of Stellenbosch}

```

Holder macros that are set by the language setup.

```

45 \newcommand\USName{}

```

Thesis Description

```

46 \newcommand\PhDDescriptAFR{%
47 \ThesisType\ ingelewer vir die graad \US@degreeelong\ aan die \USName}
48 \newcommand\PhDFinalDescriptAFR{%
49 \ThesisType\ goedgekeur vir die graad \US@degreeelong\ aan die \USName}
50 \newcommand\MastersDescriptAFR{%
51 \ThesisType\ ingelewer ter gedeeltelike voldoening aan die vereistes vir die
52 graad \US@degreeelong\ aan die \USName}
53 \newcommand\PhDDescriptENG{%
54 \ThesisType\ presented for the degree of \US@degreeelong\ at the \USName}
55 \newcommand\PhDFinalDescriptENG{%
56 \ThesisType\ approved for the degree of \US@degreeelong\ at the \USName}}
57 \newcommand\MastersDescriptENG{%
58 \ThesisType\ presented in partial fulfilment of the requirements for the degree
59 of \US@degreeelong\ at the \USName}

```

```

\MastersDescript
\PhDDescript
\PhDFinalDescript

```

```

60 \newcommand\MastersDescript{}
61 \newcommand\PhDDescript{}
62 \newcommand\PhDFinalDescript{}

```

Study leader & promotor

```

63 \newcommand\StudyLeaderAFR{Studieleier:}
64 \newcommand\StudyLeadersAFR{Studieleiers:}
65 \newcommand\PromotorAFR{Promotor:}
66 \newcommand\PromotorsAFR{Promotors:}

67 \newcommand\StudyLeaderENG{Supervisor:}
68 \newcommand\StudyLeadersENG{Supervisors:}
69 \newcommand\PromotorENG{Promoter:}
70 \newcommand\PromotorsENG{Promoters:}

```

```

\StudyLeaderType
\StudyLeadersType
  \PromotorType
  \PromotorsType
71 \newcommand\StudyLeaderType{}
72 \newcommand\StudyLeadersType{}
73 \newcommand\PromotorType{}
74 \newcommand\PromotorsType{}

```

Thesis types

```

75 \newcommand\TypeReportAFR{Verslag}
76 \newcommand\TypeAssignmentAFR{Werkstuk}
77 \newcommand\TypeThesisAFR{Tesis}
78 \newcommand\TypePhDAFR{Proefschrift}

79 \newcommand\TypeReportENG{Report}
80 \newcommand\TypeAssignmentENG{Assignment}
81 \newcommand\TypeThesisENG{Thesis}
82 \newcommand\TypePhDENG{Dissertation}

83 \newcommand\TypeReport{}
84 \newcommand\TypeAssignment{}
85 \newcommand\TypeThesis{}
86 \newcommand\TypePhD{}

```

Month names

```

87 \newcommand\MonthAFR[1]{\ifcase#1\or
88   Januarie\or Februarie\or Maart\or April\or Mei\or Junie\or
89   Julie\or Augustus\or September\or Oktober\or November\or
90   Desember\fi}

91 \newcommand\MonthENG[1]{\ifcase#1\or
92   January\or February\or March\or April\or May\or June\or
93   July\or August\or September\or October\or November\or
94   December\fi}

95 \newcommand\MonthName[1]{}

```

Copyright

```

96 \newcommand\CopyrightHolderAFR{\USName}%
97 \newcommand\CopyrightTxtAFR{Kopiereg}
98 \newcommand\CopyrightAnotAFR{Alle regte voorbehou.}

99 \newcommand\CopyrightHolderENG{\USName}

```

```

100 \newcommand\CopyrightTxtENG{Copyright}
101 \newcommand\CopyrightAnotENG{All rights reserved.}

102 \newcommand\CopyrightHolder{}
103 \newcommand\CopyrightTxt{}
104 \newcommand\CopyrightAnot{}

```

Declaration

```

105 \newcommand\ThesisDeclareAFR{%
106   Ek, die ondergetekende, verklaar hiermee dat die werk in
107   hierdie \MakeLowercase{\ThesisType}{} vervat, my eie
108   oorspronklike werk is en dat ek dit nie van te vore in
109   geheel of gedeeltelik by enige universiteit ter verkryging
110   van 'n graad voorgel\^{e} het nie.}
111 \newcommand\SignatAFR{Handtekening}
112 \newcommand\DateAFR{Datum}
113 \newcommand\ThesisDeclareENG{%
114   I, the undersigned, hereby declare that the work contained
115   in this \MakeLowercase{\ThesisType}{} is my own original
116   work and that I have not previously in its entirety or in
117   part submitted it at any university for a degree.}
118 \newcommand\SignatENG{Signature}
119 \newcommand\DateENG{Date}
120 \newcommand\ThesisDeclare{}
121 \newcommand\Signat{}
122 \newcommand\Datetxt{}

```

The holder commands

Enclose all the commands into a single command that can be used to change all the language text simultaneously.

`\USextrasafrikaans`

```

123 \newcommand{\USextrasafrikaans}{%
124   \let\USName          =\USNameAFR
125   \let\MasterDescript  =\MastersDescriptAFR
126   \let\PhDDescript     =\PhDDescriptAFR
127   \let\PhDFinalDescript=\PhDFinalDescriptAFR
128   \let\StudyLeaderType =\StudyLeaderAFR
129   \let\StudyLeadersType=\StudyLeadersAFR
130   \let\PromotorType     =\PromotorAFR
131   \let\PromotorsType    =\PromotorsAFR
132   \let\TypeReport       =\TypeReportAFR
133   \let\TypeAssignment   =\TypeAssignmentAFR
134   \let\TypeThesis       =\TypeThesisAFR
135   \let\TypePhD          =\TypePhDAFR
136   \let\MonthName        =\MonthAFR
137   \let\CopyrightHolder  =\CopyrightHolderAFR
138   \let\CopyrightTxt     =\CopyrightTxtAFR
139   \let\CopyrightAnot    =\CopyrightAnotAFR
140   \let\ThesisDeclare    =\ThesisDeclareAFR
141   \let\Signat           =\SignatAFR
142   \let\Datetxt          =\DateAFR
143 }

```

\UScaptionsafrikaans Afrikaans captions

```

144 \newcommand{\UScaptionsafrikaans}{%
145   \def\declarationname{Verklaring}%
146   \def\abstractname{Uittreksel}%
147   }

```

\USextrasenglish English code:

```

148 \newcommand{\USextrasenglish}{%
149   \let\USName          =\USNameENG
150   \let\MasterDescript  =\MastersDescriptENG
151   \let\PhDDescript     =\PhDDescriptENG
152   \let\PhDFinalDescript=\PhDFinalDescriptENG
153   \let\StudyLeaderType =\StudyLeaderENG
154   \let\StudyLeadersType=\StudyLeadersENG
155   \let\PromotorType    =\PromotorENG
156   \let\PromotorsType   =\PromotorsENG
157   \let\TypeReport      =\TypeReportENG
158   \let\TypeAssignment  =\TypeAssignmentENG
159   \let\TypeThesis      =\TypeThesisENG
160   \let\TypePhD         =\TypePhDENG
161   \let\MonthName       =\MonthENG
162   \let\CopyrightHolder =\CopyrightHolderENG
163   \let\CopyrightTxt    =\CopyrightTxtENG
164   \let\CopyrightAnot   =\CopyrightAnotENG
165   \let\ThesisDeclare   =\ThesisDeclareENG
166   \let\Signat          =\SignatENG
167   \let\Datetxt         =\DateENG
168   }

```

\UScaptionsenglish English captions

```

169 \newcommand{\UScaptionsenglish}{%
170   \def\declarationname{Declaration}%
171   \def\abstractname{Abstract}%
172   }

```

Set English as default if no language option is selected.

```

173 \USextrasenglish
174 \UScaptionsenglish

```

Set language options

\US@addto A redefinition of the babel \addto command (taken from varioref).

```

175 \def\US@addto#1#2{%
176   #2%
177   \@temptokena{#2}%
178   \ifx#1\relax
179     \let#1\@empty
180   \fi
181   \ifx#1\undefined
182     \edef#1{\the\@temptokena}%
183   \else
184     \toks@\expandafter{#1}%
185     \edef#1{\the\toks@\the\@temptokena}%

```

```

186 \fi
187 \@temptokena{}\toks@\@temptokena}

```

\US@addlangextras Add the language definitions to \extras<lang> and \captions<lang> at the beginning of the document after babel.

```

188 \newcommand\US@addlangextras[2]{%
189   \AtBeginDocument{%
190     \expandafter\US@addto\csname extras#1\endcsname #2}}
191 \newcommand\US@addlangcaptions[2]{%
192   \AtBeginDocument{%
193     \expandafter\US@addto\csname captions#1\endcsname #2}}

```

Set all the different English language options.

```

194 \DeclareOption{english}{%
195   \edef\US@ENGstr{\string english}%
196   \US@addlangextras{english}{\USextrasenglish}%
197   \US@addlangcaptions{english}{\UScaptionsenglish}}
198 \DeclareOption{UKenglish}{%
199   \edef\US@ENGstr{\string UKenglish}%
200   \US@addlangextras{UKenglish}{\USextrasenglish}%
201   \US@addlangcaptions{UKenglish}{\UScaptionsenglish}}
202 \DeclareOption{USenglish}{%
203   \edef\US@ENGstr{\string USenglish}%
204   \US@addlangextras{USenglish}{\USextrasenglish}%
205   \US@addlangcaptions{USenglish}{\UScaptionsenglish}}
206 \DeclareOption{british}{%
207   \edef\US@ENGstr{\string british}%
208   \US@addlangextras{british}{\USextrasenglish}%
209   \US@addlangcaptions{british}{\UScaptionsenglish}}

```

Set Afrikaans language option.

```

210 \DeclareOption{afrikaans}{%
211   \US@addlangextras{afrikaans}{\USextrasafrikaans}%
212   \US@addlangcaptions{afrikaans}{\UScaptionsafrikaans}}

```

4.2.2 Thesis type options

\if@Report Flag for report option.

```

213 \newif\if@Report
214 \@Reporttrue

```

\if@Masters Flag for master-a and master-t options.

```

215 \newif\if@Masters
216 \@Mastersfalse

```

\if@PhD Flag for PhD and PhDfinal options.

```

217 \newif\if@PhD
218 \@PhDfalse

```

\if@Final Flag for PhDfinal option.

```

219 \newif\if@Final
220 \@Finalfalse

```



```

\ThesisType   Global headings that are set according to the thesis type options.
\PromotorText 221 \newcommand{\ThesisType}{}
\PromotersText 222 \newcommand{\PromotorText}{}
                223 \newcommand{\PromotersText}{}

                report: For normal reports an assignments.
224 \DeclareOption{report}{%
225   \renewcommand{\ThesisType}{\TypeReport}%
226   \renewcommand{\PromotorText}{\StudyLeaderType}
227   \renewcommand{\PromotersText}{\StudyLeadersType}
228   \@Reporttrue
229   \@Mastersfalse
230   \@PhDfalse}

                masters-a: Masters with and assignment.
231 \DeclareOption{masters-a}{%
232   \renewcommand{\ThesisType}{\TypeAssignment}%
233   \renewcommand{\PromotorText}{\StudyLeaderType}
234   \renewcommand{\PromotersText}{\StudyLeadersType}
235   \@Reportfalse
236   \@Masterstrue
237   \@PhDfalse}

                masters-t: Masters with a thesis.
238 \DeclareOption{masters-t}{%
239   \renewcommand{\ThesisType}{\TypeThesis}%
240   \renewcommand{\PromotorText}{\StudyLeaderType}%
241   \renewcommand{\PromotersText}{\StudyLeadersType}%
242   \@Reportfalse
243   \@Masterstrue
244   \@PhDfalse}

                PhD: PhD dissertation handed in for examination.
245 \DeclareOption{PhD}{%
246   \renewcommand{\ThesisType}{\TypePhD}%
247   \renewcommand{\PromotorText}{\PromotorType}%
248   \renewcommand{\PromotersText}{\PromotersType}%
249   \@Reportfalse
250   \@Mastersfalse
251   \@PhDtrue
252   \@Finalfalse}

                PhDfinal: Excepted PhD dissertation handed in for publication.
253 \DeclareOption{PhDfinal}{%
254   \renewcommand{\ThesisType}{\TypePhD}%
255   \renewcommand{\PromotorText}{\PromotorType}%
256   \renewcommand{\PromotersText}{\PromotersType}%
257   \@Reportfalse
258   \@Mastersfalse
259   \@PhDtrue
260   \@Finaltrue}

```

4.2.3 Page layout options

Intercept 2-column requests.

```

261 <*cls>
262 \DeclareOption{twocolumn}{}
263 </cls>

\if@ABlock  Flags for a5block and goldenblock options.
\if@GBlock  264 \newif\if@ABlock
265 \newif\if@GBlock
266 \@ABlockfalse
267 \@GBlockfalse

a5block: An A5 type block area.
268 \DeclareOption{a5block}{%
269 <cls> \PassOptionsToClass{a4paper}{\US@basetype}%
270 \@ABlocktrue
271 \@GBlockfalse}

goldenblock: A golden section type block area.
272 \DeclareOption{goldenblock}{%
273 <cls> \PassOptionsToClass{a4paper}{\US@basetype}%
274 \@GBlocktrue
275 \@ABlockfalse}

stdblock: Standard LATEX type block area.
276 \DeclareOption{stdblock}{%
277 \@GBlockfalse
278 \@ABlockfalse}

```

4.2.4 Process package options

```

279 <cls> \DeclareOption*{\PassOptionsToClass{\CurrentOption}{\US@basetype}}
280 \ExecuteOptions{report}
281 \ProcessOptions*\relax
282 <cls> \LoadClass[oneside,openany]{\US@basetype}

```

4.3 External packages

```

283 \RequirePackage{calc}

\phantomsection  A command needed, if the hyperref package is used, for putting before certain
\addcontentsline commands.

284 \providecommand{\phantomsection}{}

\ifpdf  We need the ifpdf package, but to reduce dependencies we provide the code here
to check if a document is being processed by LATEX or pdfLATEX. It is all ready
declared by memoir.

285 <*cls>
286 \newif\ifpdf
287 \ifx\pdfoutput\undefined
288 \else
289 \ifx\pdfoutput\relax
290 \else
291 \ifcase\pdfoutput
292 \else
293 \pdftrue
294 \fi

```

```

295 \fi
296 \fi
297 \end{cls}

```

We need the `graphicx` package and it must be loaded by the user in the document preamble.

```

298 \AtBeginDocument{%
299   \ifpackageloaded{graphicx}{}{%
300   \cls} \ClassError{usthesis}{You must load the graphicx package}{}%
301   \ifpackageloaded{graphicx}{}{%
302   \cls} \PackageError{usthesis}{You must load the graphicx package}{}%
303   }%
304 }

```

4.4 Temporaries

```

304 \newlength{\US@tdima}
305 \newlength{\US@tdimb}
306 \newsavebox{\US@tboxa}
307 \newcounter{\US@tcnta}
308 \newcounter{\US@tcntb}

```

4.5 Page layout

`\FixVertParams` Reset all the vertical parameters for a page layout. Note that memoir has its own setup.

```

309 \begin{cls}
310 \newcommand\FixVertParams[1]{%
311   \normalsize
312   \setlength\US@tdima{\textheight-\topskip}%
313   \setcounter{\US@tcnta}{\US@tdima}
314   \setcounter{\US@tcntb}{\baselineskip}
315   \setcounter{\US@tcnta}{\value{\US@tcnta}/\value{\US@tcntb}}
316   \setlength\textheight{\baselineskip*\value{\US@tcnta}+\topskip}%
317   \setlength\US@tdima{\paperheight-\textheight}%
318   \setlength\topmargin{#1\US@tdima-\headheight-\headsep-1in}%
319   \settopoint\topmargin}
320 \end{cls}

```

`\FixHorizParams` Reset all the horizontal parameters for a page layout. Note that memoir has its own setup.

```

321 \begin{cls}
322 \newcommand\FixHorizParams[1]{%
323   \settopoint\textwidth
324   \setlength\US@tdima{\paperwidth-\textwidth}%
325   \if@twoside
326     \setlength\oddsidemargin{#1\US@tdima-1in}%
327   \else
328     \setlength\oddsidemargin{.5\US@tdima-1in}%
329   \fi
330   \settopoint\oddsidemargin
331   \setlength\evensidemargin{\US@tdima-\oddsidemargin-2in}%
332   \settopoint\evensidemargin
333   \setlength\marginparwidth{\evensidemargin+1in-\marginparsep-1cm}%
334   \settopoint\marginparwidth}

```

```
335 </cls>
```

4.5.1 A5 type block area

```
336 <*cls>
337 \if@ABlock
338   \setlength\paperheight {297.3mm}
339   \setlength\paperwidth  {210.2mm} % A4 paper
340   \setlength\textwidth   {.5\paperheight}
341   \setlength\textheight  {\paperwidth}
342   \setlength\marginparsep {7\p@}
343   \setlength\marginparpush{7\p@}
344   \FixVertParams{0.375}
345   \FixHorizParams{0.375}
346   \ifpdf
347     \setlength\pdfpagewidth{\paperwidth}
348     \setlength\pdfpageheight{\paperheight}
349   \fi
350 \fi
351 </cls>
352 <*mem>
353 \if@ABlock
354   \setstocksize{297.3mm}{210.2mm}% A4 paper
355   \settrimmedsize{\stockheight}{\stockwidth}{*}
356   \settypeblocksize{\paperwidth}
357     {.5\paperheight}{*}% A5 text block
358   \setulmargins{*}{*}{1.666667} % 5:3
359   \if@twoside
360     \setlrmargins{*}{*}{1.666667} % 5:3
361   \else
362     \setlrmargins{*}{*}{1.000000} % 1:1
363   \fi
364   \checkandfixthelayout
365   \setlength{\headwidth}{\textwidth}
366 \fi
367 </mem>
```

4.5.2 Golden section type block area

```
368 <*cls>
369 \if@GBlock
370   \setlength\paperheight {297.3mm}
371   \setlength\paperwidth  {210.2mm} % A4 paper
372   \setlength\textheight  {0.747547\paperheight}
373   \setlength\textwidth   {0.666667\paperwidth}
374   \setlength\marginparsep {7\p@}
375   \setlength\marginparpush{7\p@}
376   \FixVertParams{0.375}
377   \FixHorizParams{0.375}
378   \ifpdf
379     \setlength\pdfpagewidth{\paperwidth}
380     \setlength\pdfpageheight{\paperheight}
381   \fi
382 \fi
383 </cls>
```

```

384 (*mem)
385 \if@GBlock
386     \setstocksize{297.3mm}{210.2mm}
387     \settrimmedsize{\stockheight}{\stockwidth}{*}
388     \settypeblocksize{0.747547\paperheight}
389         {0.666667\paperwidth}{*}% Golden ratio block
390     \setulmargins{*}{*}{1.666667} % 5:3
391     \if@twoside
392         \setlrmargins{*}{*}{1.666667} % 5:3
393     \else
394         \setlrmargins{*}{*}{1.000000} % 1:1
395     \fi
396     \checkandfixthelayout
397     \setlength{\headwidth}{\textwidth}
398 \fi
399 </mem>

```

4.6 Utility commands

\US@ifempt Test for a empty argument (Wilson, Arseneau in ifmtarg)

```

400 \begingroup
401     \catcode'\Q=3
402     \long\gdef\US@ifempt#1{\US@xifempt#1QQ\@secondoftwo\@firstoftwo\@nil}
403     \long\gdef\US@xifempt#1#2Q#3#4#5\@nil{#4}
404 \endgroup

```

US@adjustwidth Adjust the width of a paragraph. It differs from the memoir environment **AdjustWidth** in that all top and bottom spaces are removed.

```

405 \newenvironment{US@adjustwidth}[2]{%
406     \begin{list}{}{%
407         \setlength{\topsep}{0pt}%
408         \setlength{\partopsep}{0pt}%
409         \setlength{\leftmargin}{#1}%
410         \setlength{\rightmargin}{#2}%
411         \setlength{\listparindent}{\parindent}%
412         \setlength{\itemindent}{\parindent}%
413         \setlength{\parsep}{\parskip}%
414     }%
415     \item[]{\end{list}}

```

SetMargins Adjust the margins of a paragraph. The parameter **#1** and **#2** are the left and right margins of the paragraph.

```

416 \newenvironment{SetMargins}[2]{%
417     {\setlength{\US@tdima}{-1in-\hoffset-\oddsidemargin}%
418     \setlength{\US@tdimb}{-\US@tdima}%
419     \addtolength{\US@tdima}{#1}%
420     \addtolength{\US@tdimb}{-\paperwidth+\textwidth+#2}%
421     \begin{US@adjustwidth}{\US@tdima}{\US@tdimb}%
422     }%
423     {\end{US@adjustwidth}}

```

4.7 Front pages

4.7.1 Title page

`US@titlepage` Make a single column empty page with predefined margins

```

\begin{US@titlepage}{\top}{\bottom}{\left}{\right}
  \langle title page \rangle
\end{US@titlepage}

424 \newenvironment{US@titlepage}[4]
425   {\cleardoublepage
426     \if@twocolumn
427       \@restonecoltrue\onecolumn
428     \else
429       \@restonecolfalse\newpage
430     \fi
431     \thispagestyle{empty}%
432     \setcounter{page}\@ne

      Set the top margin by moving the starting point up.

433     \setlength{\US@tdima}{1in+\voffset+\topmargin+\headheight+\headsep+\topskip}%
434     \setlength{\US@tdimb}{\#1 -\US@tdima}%
435     \vspace*{\US@tdimb}%

      Set the bottom margin by enlarging the page

436     \addtolength{\US@tdima}{\textheight-\paperheight-\topskip}%
437     \addtolength{\US@tdima}{\#2}%
438     \enlargethispage{-\US@tdima}%

      Set the left and right margins by putting the contents in a list environ-
      ment with widened margins.

439     \setlength{\US@tdima}{-1in-\hoffset-\oddsidemargin}%
440     \setlength{\US@tdimb}{-\US@tdima}%
441     \addtolength{\US@tdima}{\#3}%
442     \addtolength{\US@tdimb}{-\paperwidth+\textwidth+\#4}%
443     \begin{US@adjustwidth}{\US@tdima}{\US@tdimb}%
444   }%
445   {\end{US@adjustwidth}%
446     \if@restonecol\twocolumn \else \newpage \fi
447     \if@twoside\else
448       \setcounter{page}\@ne
449     \fi}

      Undefine the standard title page.
450 \let\maketitle\relax

```

The title page

`\TitlePage` The `\TitlePage` command set the full front page for the US theses and reports. All margins, spacing and font sizes must be set inside this command.

```

451 \newcommand{\TitlePage}{%
452   \begin{group}
453     \let\footnote\relax
454     \begin{US@titlepage}{2cm}{2.5cm}{2.5cm}{2.5cm}%

```

```

455     \centering
456     \if@Report
457         \includegraphics[width=100mm]{USlogo-top}\par
458     \else
459         %\includegraphics[width=88mm]{UScrest-top}\par
460     \fi
461     \vfill
462     {\LARGE \@title \par}
463     \vspace{2em}
464     \if@Authorpresent
465         {\large \AorE{deur}{by}\par}
466         \vspace{2em}
467         {\Large
468             \lineskip .75em\relax%
469             \begin{tabular}[t]{c}%
470                 \US@authorlong
471             \end{tabular}\par}%
472         \vfill
473     \fi
474     {\large\slshape
475         \begin{US@adjustwidth}{1.5cm}{1.5cm}
476             \centering\US@ThesisDescript
477         \end{US@adjustwidth}\par}
478     \vfill
479     {\US@adress\par}
480     \vfill
481     {\normalsize \US@promotorset \par}
482     \vfill
483     {\large \US@date\par}%
484     \end{US@titlepage}%
485 \endgroup
486 \global\let\TitlePage\relax
487 \setcounter{footnote}{0}%
488 \global\let\thanks\relax
489 \global\let\@thanks\@empty
490 % \global\let\and\relax
491 }

```

Author block

```

492 \newif\if@Authorpresent
493 \@Authorpresentfalse
494 \renewcommand\author[2]{%
495     \@Authorpresenttrue%
496     \gdef\US@author{#1}%
497     \gdef\US@authorlong{#2}}
498 \newcommand\US@author{%
499 <cls> \ClassWarning{usthesis}{No author supplied}%
500 <mem> \PackageWarning{usthesis}{No author supplied}%
501 }
502 \newcommand\US@authorlong{%
503 <cls> \ClassWarning{usthesis}{No author supplied}%
504 <mem> \PackageWarning{usthesis}{No author supplied}%

```

505 }

Thesis or report description

506 \newcommand{\US@ThesisDescript}{}

\ThesisDescript

507 \newcommand\ThesisDescript[1]{%

508 \long\gdef\US@ThesisDescript{#1}}

509 \let\ReportDescript=\ThesisDescript

510 \if@Masters

511 \ThesisDescript{\MasterDescript}

512 \fi

513 \if@PhD

514 \if@Final

515 \ThesisDescript{\PhDFinalDescript}

516 \else

517 \ThesisDescript{\PhDDescript}%

518 \fi

519 \fi

Degree or subject

See beginning of class for \US@degree and \US@degreeelong.

520 \newcommand\degree[2]{%

521 \gdef\US@degree{#1}%

522 \gdef\US@degreeelong{#2}}

523 \let\subject=\degree

Address

524 \newcommand\address[1]{\gdef\US@address{#1}}

525 \newcommand\US@address{%

526 \cls) \ClassWarning{usthesis}{No institutional address supplied}}

527 \mem) \PackageWarning{usthesis}{No institutional address supplied}}

Promotor or study leader

528 \newif\ifUS@multprm\US@multprmfalse

529 \newif\ifUS@prmstacked\US@prmstackedfalse

530 \newcommand\US@promotor{}

531 \newcommand*\US@prmalign{1}

532 \newcommand*\US@prmnewline{~}

\promotor

533 \newcommand{\promotor}{%

534 \@ifstar{\US@prmstackedtrue\@promotor}%

535 {\US@prmstackedfalse\@promotor}}

536 \newcommand{\@promotor}[2][1]{%

537 \renewcommand*\US@prmalign{#1}%

538 \renewcommand\US@promotor{#2}}


```

539 \newcommand{\US@promotorset}{%
540   \edef\US@beginTab{%
541     \noexpand\begin{tabular}[t]{@{} \US@prmalign @{}}}%
542   \edef\US@endTab{%
543     \noexpand\end{tabular}}%
544   \sbox{\US@tboxa}{%
545     \let\and\US@prm@and%
546     \US@beginTab%
547     \US@promotor%
548     \US@endTab}%
549   \ifUS@prmstacked
550     \makebox[\wd\US@tboxa][\US@prmalign]{%
551       \ifUS@multprm\PromotorsText\else\PromotorText\fi}\[1ex]%
552     \usebox{\US@tboxa}%
553   \else
554     \ifUS@multprm\PromotorsText\else\PromotorText\fi
555     \US@prmnewline%
556     \usebox{\US@tboxa}%
557   \fi
558 }

559 \newcommand*{\US@prm@and}[1][2ex]{%
560   \gdef\US@prmnewline{\[2ex]}%
561   \global\US@multprmtrue%
562   \ifUS@prmstacked
563     \[1ex]%
564   \else
565     \US@endTab
566     \hskip 1em \@plus.17fil\relax
567     \US@beginTab
568   \fi
569   \ignorespaces}

570 \let\studyleader\promotor
571 \let\supervisor\promotor

```

Date

```

572 \newcount\US@month
573 \newcount\US@year

574 \US@month=0
575 \US@year=\number\year
576 \def\US@date{\MonthName{\US@month}\ \number\US@year}

577 \newcommand{\setdate}[2]{%
578   \US@ifempty{#1}{\US@month=0}{\US@month=#1}%
579   \US@year=#2
580   \gdef\US@date{\MonthName{\US@month}\ \number\US@year}}

```

4.7.2 Copyright page

```

581 \newcommand\CopyrightPage[1][\CopyrightHolder]{%
582   \clearpage
583   \thispagestyle{empty}
584   \mbox{}\par\vfill
585   \begin{center}

```

```

586     \CopyrightTxt\ \copyright\ \number\US@year\ #1\
587     \CopyrightAnot
588 \end{center}
589 \vfill\mbox{}\par
590 \clearpage}

```

4.7.3 Declaration page

`\DeclarationPage` Set up the declaration page. The `\ThesisDeclare[⟨declaration⟩]` command has an optional argument to set a different declaration.

```

591 \newcommand{\DeclarationPage}[1][\ThesisDeclare]{%
592   \if@twocolumn
593     \@restonecoltrue\onecolumn
594   \else
595     \@restonecolfalse
596   \fi
597   \par
598   \thispagestyle{plain}%
599   \chapter*{\declarationname}%
600   \declaremark
601   \phantomsection
602   \addcontentsline{toc}{chapter}{\declarationname}%
603   #1\par
604   \vspace{3cm}
605   \noindent
606   \begin{minipage}{.5\textwidth}
607     \Signat:~\dotfill\mbox{}\
608     \phantom{\Signat:}~%
609     \hfill\makebox[0pt][c]{\US@author}\hfill\mbox{}\
610     \Datetxt:~\dotfill\mbox{}
611   \end{minipage}
612   \if@restonecol\twocolumn\fi}

```

4.7.4 Abstract page

`abstract` Provides the environment

```

\begin{abstract}[⟨lang⟩]
  ⟨abstract text⟩
\end{abstract}

```

to typeset the abstract. A different language can be selected with the optional argument to the environment.

```

613 ⟨cls⟩\newenvironment{abstract}[1][\language]{%
614 ⟨mem⟩\renewenvironment{abstract}[1][\language]{%
615   {\edef\@tempa{\expandafter\string #1}%
616   \ifx\@tempa\language\relax\else
617     \edef\@tempa{\noexpand\selectlanguage{#1}}\@tempa%
618   \fi
619   \if@twocolumn
620     \@restonecoltrue\onecolumn
621   \else
622     \@restonecolfalse
623   \fi
624   \par

```

```

625 \chapter*{\abstractname}%
626 \abstractmark
627 \phantomsection
628 \addcontentsline{toc}{chapter}{\abstractname}%
629 \if@Report\else
630 \begin{center}
631 {\large\bfseries \@title \par}
632 \medskip
633 {\lineskip .75em\relax%
634 \begin{tabular}[t]{@{}c@{}}%
635 \US@author
636 \end{tabular}\par}
637 \smallskip
638 {\small\itshape\US@adress\par}
639 \smallskip
640 {\ThesisType: \US@degree\par}
641 \smallskip
642 {\US@date\par}
643 \end{center}
644 \fi
645 \if@restonecol\twocolumn\fi%
646 }{}

```

4.7.5 Table of contents

```

647 <*cls>
648 \renewcommand\tableofcontents{%
649 \if@twocolumn
650 \@restonecoltrue\onecolumn
651 \else
652 \@restonecolfalse
653 \fi
654 \chapter*{\contentsname}%
655 \tocmark
656 \phantomsection
657 \addcontentsline{toc}{chapter}{\contentsname}%
658 \@starttoc{toc}%
659 \if@restonecol\twocolumn\fi}
660 </cls>

```

4.7.6 List of figures

```

661 <*cls>
662 \renewcommand\listoffigures{%
663 \if@twocolumn
664 \@restonecoltrue\onecolumn
665 \else
666 \@restonecolfalse
667 \fi
668 \chapter*{\listfigurename}%
669 \lofmark
670 \phantomsection
671 \addcontentsline{toc}{chapter}{\listfigurename}%
672 \@starttoc{lof}%
673 \if@restonecol\twocolumn\fi

```

```

674     }
675 \renewcommand*\l@figure{\@dottedtocline{1}{0em}{3em}}
676 \</cls>

```

4.7.7 List of tables

```

677 \<cls>
678 \renewcommand\listoftables{%
679     \if@twocolumn
680         \@restonecoltrue\onecolumn
681     \else
682         \@restonecolfalse
683     \fi
684     \chapter*\listtablename}%
685     \lotmark
686     \phantomsection
687     \addcontentsline{toc}{chapter}{\listtablename}%
688     \@starttoc{lot}%
689     \if@restonecol\twocolumn\fi}
690 \let\l@table\l@figure
691 \</cls>

```

4.8 Back matter

4.8.1 Bibliography

`\bibsection` natbib uses the `\bibsection` command. We change the `thebibliography` to use it also.

```

692 \<cls>
693 \providecommand\bibsection{}%
694 \AtBeginDocument{%
695     \renewcommand{\bibsection}{%
696         \chapter*\bibname}%
697         \bibmark
698         \phantomsection
699         \addcontentsline{toc}{chapter}{\bibname}}%
700     }
701 \</cls>

```

`thebibliography` The environment is a mixture of code from `book.cls` and `natbib`

```

702 \<cls>
703 \renewenvironment{thebibliography}[1]{%
704     \bibsection
705     \parindent \z@
706     \bibpreamble
707     \bibfont
708     \list{\@biblabel{\@arabic{c@enumiv}}}%
709         {\settowidth\labelwidth{\@biblabel{#1}}%
710         \leftmargin\labelwidth
711         \advance\leftmargin\labelsep
712         \@openbib@code
713         \usecounter{enumiv}%
714         \let\p@enumiv\@empty
715         \renewcommand\theenumiv{\@arabic{c@enumiv}}}%
716     \sloppy

```

```

717 \clubpenalty4000
718 \@clubpenalty \clubpenalty
719 \widowpenalty4000%
720 \sfcode\.\@m}
721 {\def\@noitemerr%
722   {\@latex@warning{Empty thebibliography environment}}}%
723 \endlist
724 \vskip-\lastskip}
725 </cls>

```

`\bibfont` Command to change font sizes.

`\bibpreamble` The user can add stuff before the bibliography.

```

726 <*cls>
727 \let\bibfont\relax
728 \let\bibpreamble\relax
729 </cls>

```

`\setbiblabel` A user command to change the bib label format .

```

730 <*cls>
731 \newcommand*{\setbiblabel}[1]{%
732   \renewcommand*{\@biblabel}[1]{#1}}
733 \setbiblabel{[#1]\hfill}
734 </cls>

```

4.8.2 Index

`theindex`

```

735 <*cls>
736 \renewenvironment{theindex}
737   {\if@twocolumn
738     \@restonecolfalse
739   \else
740     \@restonecoltrue
741   \fi
742   \columnseprule \z@
743   \columnsep 35\p@
744   \twocolumn[\@makeschapterhead{\indexname}]}%
745   \indexmark
746   \phantomsection
747   \addcontentsline{toc}{chapter}{\indexname}
748   \thispagestyle{plain}
749   \parindent\z@
750   \parskip\z@ \@plus .3\p@\relax
751   \let\item\@idxitem}
752   {\if@restonecol
753     \onecolumn
754   \else
755     \clearpage
756   \fi}
757 </cls>

```

4.9 Page markup

4.9.1 Headers and footers

`\US@headfnt` Font for running headers.

`\US@numfnt` Font for running header numbers.

```
758 \newcommand*{\US@headfnt}[1]{\slshape\small#1}
```

```
759 \newcommand*{\US@numfnt}[1]{\normalsize\bfseries#1}
```

Define the `usthesis` page style The setup for headers and footers differs between the normal book class and memoir, therefor we split them up.

Headers for normal book class

```
760 \*cls)
761 \if@twoside
762   \def\ps@usthesis{%
763     \def\@evenhead{\US@numfnt{\thepage}\hfil\US@headfnt{\leftmark}}%
764     \def\@oddhead{\US@headfnt{\rightmark}\hfil\US@numfnt{\thepage}}%
765     \let\@oddfoot\@empty
766     \let\@evenfoot\@empty
767     \let\@mkboth\markboth
768     \def\chaptermark##1{%
769       \markboth{\MakeUppercase{
770         \ifnum \c@secnumdepth > \m@ne
771           \if@mainmatter
772             \@chapapp\ thechapter. \ %
773             \fi
774           \fi
775         ##1}}}%
776     \def\sectionmark##1{%
777       \markright{\MakeUppercase{
778         \ifnum \c@secnumdepth > \z@
779           \thesection. \ %
780           \fi
781         ##1}}}%
782     \def\declaremark{\markboth{\MakeUppercase{\declarationname}}}%
783     \def\abstractmark{\markboth{\MakeUppercase{\abstractname}}}%
784     \def\tocmark{\markboth{\MakeUppercase{\contentsname}}}%
785     \def\lofmark{\markboth{\MakeUppercase{\listfigurename}}}%
786     \def\lotmark{\markboth{\MakeUppercase{\listtablename}}}%
787     \def\bibmark{\markboth{\MakeUppercase{\bibname}}}%
788     \def\indexmark{\markboth{\MakeUppercase{\indexname}}}%
789   }
790 \else
791   \def\ps@usthesis{%
792     \def\@oddhead{\US@headfnt{\rightmark}\hfil\US@numfnt{\thepage}}%
793     \let\@oddfoot\@empty
794     \let\@mkboth\markboth
795     \def\chaptermark##1{%
796       \markright{\MakeUppercase{
797         \ifnum \c@secnumdepth > \m@ne
798           \if@mainmatter
799             \@chapapp\ thechapter. \ %
800             \fi
```

```

801         \fi
802         ##1}}}%
803     \def\declaremark{\markright{\MakeUppercase{\declarationname}}}%
804     \def\abstractmark{\markright{\MakeUppercase{\abstractname}}}%
805     \def\tocmark{\markright{\MakeUppercase{\contentsname}}}%
806     \def\lofmark{\markright{\MakeUppercase{\listfigurename}}}%
807     \def\lotmark{\markright{\MakeUppercase{\listtablename}}}%
808     \def\bibmark{\markright{\MakeUppercase{\bibname}}}%
809     \def\indexmark{\markright{\MakeUppercase{\indexname}}}%
810 }
811 \fi

Redefine the plain page style.
812 \def\ps@plain{%
813     \let\@mkboth\@gobbletwo
814     \let\@oddhead\@empty
815     \let\@evenhead\@empty
816     \def\@oddfoot{\reset@font\hfil\US@numfnt{\thepage}\hfil}%
817     \let\@evenfoot\@oddfoot
818 }
819 \</cls>

Headers for use with memoir class
820 (*mem)
821 \makepagestyle{usthesis}

822 \setlength{\headwidth}{\textwidth}
823 \makerunningwidth{usthesis}{\headwidth}
824 \makeheadposition{usthesis}{flushright}{flushleft}{flushright}{flushleft}

825 \if@twoside
826     \makepsmarks{usthesis}{%
827         \let\@mkboth\markboth
828         \def\chaptermark##1{%
829             \markboth{\MakeUppercase{%
830                 \ifnum \c@secnumdepth > \m@ne
831                     \if@mainmatter
832                         \@chapapp\ thechapter. \ %
833                     \fi
834                     \fi
835                 ##1}}{}}%
836         \def\sectionmark##1{%
837             \markright{\MakeUppercase{%
838                 \ifnum \c@secnumdepth > \z@
839                     \thesection. \ %
840                 \fi
841                 ##1}}}%
842         \def\declaremark{\markboth{\MakeUppercase{\declarationname}}{}}}%
843         \def\abstractmark{\markboth{\MakeUppercase{\abstractname}}{}}}%
844         \def\tocmark{\markboth{\MakeUppercase{\contentsname}}{}}}%
845         \def\lofmark{\markboth{\MakeUppercase{\listfigurename}}{}}}%
846         \def\lotmark{\markboth{\MakeUppercase{\listtablename}}{}}}%
847         \def\bibmark{\markboth{\MakeUppercase{\bibname}}{}}}%
848         \def\indexmark{\markboth{\MakeUppercase{\indexname}}{}}}%
849     }
850     \makeevenhead{usthesis}{\US@numfnt{\thepage}}{\US@headfnt{\leftmark}}

```

```

851 \makeoddhead{usthesis}{\US@headfnt{\rightmark}}{\US@numfnt{\thepage}}
852 \else
853 \makepsmarks{usthesis}{%
854 \let\@mkboth\markboth
855 \def\chaptermark##1{%
856 \markright{\MakeUppercase{%
857 \ifnum \c@secnumdepth >\m@ne
858 \if@mainmatter
859 \@chapapp\ thechapter. \ %
860 \fi
861 \fi
862 ##1}}}%
863 \def\declaremark{\markright{\MakeUppercase{\declarationname}}}%
864 \def\abstractmark{\markright{\MakeUppercase{\abstractname}}}%
865 \def\tocmark{\markright{\MakeUppercase{\contentsname}}}%
866 \def\lofmark{\markright{\MakeUppercase{\listfigurename}}}%
867 \def\lotmark{\markright{\MakeUppercase{\listtablename}}}%
868 \def\bibmark{\markright{\MakeUppercase{\bibname}}}%
869 \def\indexmark{\markright{\MakeUppercase{\indexname}}}%
870 }
871 \makeoddhead{usthesis}{\US@headfnt{\rightmark}}{\US@numfnt{\thepage}}
872 \fi

```

Change the plain page style

```

873 \setlength{\headwidth}{\textwidth}
874 \makerunningwidth{plain}{\headwidth}
875 \makeevenfoot{plain}{\US@numfnt{\thepage}}
876 \makeoddfoot{plain}{\US@numfnt{\thepage}}
877 \</mem>

```

The default page style.

```
878 \pagestyle{usthesis}
```

4.9.2 Chapter and section headings

```

879 \newcommand{\US@headfamily}{\normalfont\rmfamily}
880 \<cls>
881 \def\section{%
882 \startsection{section}{1}%
883 {\z@}%
884 {-3.5ex plus -1ex minus -.2ex}%
885 {2.3ex plus .2ex}%
886 {\US@headfamily\Large\bfseries\raggedright}}
887 \</cls>
888 \<mem>
889 \setsecheadstyle{\US@headfamily\Large\bfseries\raggedright}
890 \</mem>
891 \<cls>
892 \def\subsection{%
893 \startsection{subsection}{2}%
894 {\z@}%
895 {-3.25ex plus -1ex minus -.2ex}%
896 {1.5ex plus .2ex}%
897 {\US@headfamily\large\bfseries\raggedright}}
898 \</cls>
899 \<mem>

```



```

900 \setsubsecheadstyle{\US@headfamily\large\bfseries\raggedright}
901 \</mem>

902 \<cls>
903 \def\subsubsection{%
904     \@startsection{subsubsection}{3}%
905         {\z@}%
906         {-3.25ex plus -1ex minus -.2ex}%
907         {1.5ex plus .2ex}%
908         {\US@headfamily\normalsize\bfseries\raggedright}}
909 \</cls>
910 \<mem>
911 \setsubsubsecheadstyle{\US@headfamily\normalsize\bfseries\raggedright}
912 \</mem>

913 \<cls>
914 \def\paragraph{%
915     \@startsection{paragraph}{4}%
916         {\z@}%
917         {3.25ex plus 1ex minus .2ex}%
918         {-1em}%
919         {\US@headfamily\normalsize\bfseries}}
920 \</cls>
921 \<mem>
922 \setparaheadstyle{\US@headfamily\normalsize\bfseries}
923 \</mem>

924 \<cls>
925 \def\subparagraph{%
926     \@startsection{subparagraph}{5}%
927         {\parindent}%
928         {3.25ex plus 1ex minus .2ex}%
929         {-1em}%
930         {\US@headfamily\normalsize\bfseries}}
931 \</cls>
932 \<mem>
933 \setsubparaheadstyle{\US@headfamily\normalsize\bfseries}
934 \</mem>

```

4.9.3 Floats and float pages

```

935 \setcounter{topnumber}{3}
936 \setcounter{bottomnumber}{2}
937 \setcounter{totalnumber}{4}
938 \setcounter{dbltopnumber}{3}

939 \renewcommand{\topfraction}{.85}
940 \renewcommand{\bottomfraction}{.7}
941 \renewcommand{\textfraction}{.1}
942 \renewcommand{\floatpagefraction}{.7}
943 \renewcommand{\dbltopfraction}{.85}
944 \renewcommand{\dblfloatpagefraction}{.7}

945 \setlength{\floatsep}{15pt plus 12pt}
946 \setlength{\textfloatsep}{\floatsep}
947 \setlength{\intextsep}{\floatsep}
948 \setlength{\dblfloatsep}{15pt plus 12pt}
949 \setlength{\dbltextfloatsep}{15pt plus 12pt}

```

```

950 \setlength{\@fptop}{0pt plus1fil}
951 \setlength{\@fpbot}{0pt plus1fil}
952 \setlength{\@fpsep}{8pt plus1fil}
953 \setlength{\@dblftop}{0pt plus1fil}
954 \setlength{\@dblfbot}{0pt plus1fil}
955 \setlength{\@dblfpsep}{8pt plus1fil}

```

4.9.4 Captions

Figures and tables use the same caption command in the standard `book.cls`. This causes problems with spacing, because figure captions are normally below the figure while table captions are above the table. Make the spacing equal.

Set parameters for `usthesis.cls`.

```

956 \*cls
957 \setlength{\abovecaptionskip}{0.5\baselineskip}
958 \setlength{\belowcaptionskip}{0.5\baselineskip}

```

`\@makecaption` Redefine the caption output.

```

959 \long\def\@makecaption#1#2{%
960   \vskip\abovecaptionskip
961   \sbox\@tempboxa{\small\bfseries #1:} #2}%
962   \ifdim \wd\@tempboxa >\hsize
963     \unhbox\@tempboxa\par
964   \else
965     \global \@minipagefalse
966     \hb@xt@\hsize{\hfil\box\@tempboxa\hfil}%
967   \fi
968   \vskip\belowcaptionskip}
969 \</cls>

```

Set parameter for `memoir`.

```

970 \*mem
971 \captiondelim{: }
972 \captionnamefont{\small\bfseries}
973 \captiontitlefont{\small}
974 \captionstyle{}
975 \</mem>

```

```
976 \</cls | mem>
```

The end of this package.

Change History

v0.1		v1.1b
General: Initial version	1	General: Documentation update . . . 1
v1.1		v2.0
General: Major code update	1	General: Documentation update . . . 1
		Page layout 1
v1.1a		v2.1
General: Documentation update . . . 1		General: Bug in PhD description 32

Documentation update	1	title page	32
\MastersDescript: Change mas-		\TitlePage: Change thesis descrip-	
ters description to conform with		tion	30
US requirements	20		
\promotor: Change for promo-		v2.2	
tor/colortbl bug	32	General: Change typo in supervi-	
\StudyLeaderType: Change study		sors	21
leader to supervisor	21	v2.2a	
\ThesisDescript: Move layout to		General: Documentation update . .	1