

# The `isodateo` package\*

Harald Harders  
h.harders@tu-bs.de

File Date 2004-02-12, Printed 2005-03-10

## Abstract

This package provides commands to switch between different date formats (standard, ISO, numeric, L<sup>A</sup>T<sub>E</sub>X package). They are used by the `\today` command and by the `\printdate` and `\printdateTeX` commands that print any date. This package supports German (old and new rules, Austrian), US English, and all languages that have the same date format as British English does<sup>1</sup>.

The idea for this package was taken from the `akletter` class.

## Contents

<b>1</b>	<b>Commands</b>	<b>1</b>
1.1	Switching the date format . . . . .	1
1.2	Printing any date . . . . .	2
1.3	Changing the ISO format . . . . .	2
<b>2</b>	<b>Calling the package</b>	<b>3</b>
<b>A</b>	<b>Licence</b>	<b>3</b>
<b>B</b>	<b>Known errors</b>	<b>3</b>
<b>C</b>	<b>Planned features and changes</b>	<b>3</b>
<b>D</b>	<b>The implementation</b>	<b>4</b>

## 1 Commands

### 1.1 Switching the date format

`\today` This package provides five commands to switch the output format of the `\today`,

---

\*This file has version 1.06a last revised 2004-02-12, documentation dated 2000-08-08.

<sup>1</sup>E.g. Danish, French

the `\printdate`, and the `\printdateTeX` commands:

	<code>\isodate</code>	date format described in ISO 8601 and DIN 5008 (yyyy-mm-dd)
	<code>\numdate</code>	numeric date format with four digits of the year
<code>\isodate</code>	<code>\shortdate</code>	short numeric date format with two digits of the year
<code>\numdate</code>	<code>\TeXdate</code>	date format used for version description of packages (yyyy/mm/dd)
<code>\shortdate</code>		
<code>\TeXdate</code>	<code>\origdate</code>	original L <sup>A</sup> T <sub>E</sub> X format
<code>\origdate</code>		

The numeric and short numeric format change their behaviour depending on the actual language:

German, nGerman	<code>dd.\,mm.\,yyyy</code>	resp.	<code>dd.\,mm.\,yy</code>
US English	<code>mm/dd/yyyy</code>	resp.	<code>mm/dd/yy</code>
other languages	<code>dd/mm/yyyy</code>	resp.	<code>dd/mm/yy</code>

So this package supports German (old and new rules, Austrian), US English, and all languages that have the same date format as British English does<sup>2</sup>. Switching the language by using `\selectlanguage` also switches back to the original date format.

## 1.2 Printing any date

`\printdate` The command `\printdate{#1}` prints any date in the actual format. The argument may be a date in German, British English, or ISO format, e.g.

```
\printdate{24.12.2000}
\printdate{24/12/2000}
\printdate{2000-12-24}
```

`\printdateTeX` The command `\printdateTeX{#1}` prints any date in the actual format. The argument must be in the L<sup>A</sup>T<sub>E</sub>X format `yyyy/mm/dd`, e.g.

```
\printdateTeX{2000/12/24}
```

This command is useful for printing version information stored in a macro. For example the version of this documentation is stored in the macro `\docdate` (“2000/08/08”). To print it with the actual date format you can use the command `\printdateTeX{\docdate}` which leads to “2000-08-08”.

## 1.3 Changing the ISO format

`\isodash` I am not sure whether the ISO format should be `yyyy-mm-dd` or `yyyy–mm–dd`. By default I use “-” as dash. You can change this using the `\isodash` command, e.g.

---

<sup>2</sup>E.g. Danish, French

```

\printdate{24/12/2000}
\isodash{--}
\printdate{24/12/2000}

```

leads to “2000-12-24 2000–12–24”. Or for example

```

\isodash{${\cdot}}
\printdate{24/12/2000}

```

leads to “2000·12·24”.

## 2 Calling the package

The package is called using the `\usepackage` command:

```
\usepackage[option]{isodate}.
```

The possible package options can be seen in table 1.

Table 1: Package options

option	used date format
<code>iso</code>	ISO date format
<code>num</code>	numeric date format with 4 digits of the year
<code>short</code>	numeric date format with 2 digits of the year
<code>TeX</code>	L <sup>A</sup> T <sub>E</sub> X numeric date format (yyyy/mm/dd)
<code>orig</code>	normal L <sup>A</sup> T <sub>E</sub> X date format (default)

## A Licence

Copyright 2000 Harald Harders

This program can be redistributed and/or modified under the terms of the LaTeX Project Public License Distributed from CTAN archives in directory `macros/latex/base/lppl.txt`; either version 1 of the License, or any later version.

## B Known errors

- The `\printdate` and `\printdateTeX` commands are not very good in checking the argument for correct syntax.
- For the language American: Using the package `babel` only the language name “american” works, using the package `*german` only “USenglish” works.

## C Planned features and changes

- Of course eliminate the errors.

- Add other languages then german, ngerman, english, USenglish. Please help me with this topic, I don't know the date formats in other languages.

## D The implementation

Heading of the package:

```

1 \NeedsTeXFormat{LaTeX2e}
2 \ProvidesPackage{isodate}[\filedate]
3 \RequirePackage{ifthen}
4 \RequirePackage{calc}
5 \IfFileExists{substr.sty}{\RequirePackage{substr}%
6 }{\PackageError{isodate.sty}{Package file substr.sty not found}
7   {This version of isodate.sty needs the package substr.sty.^^J%
8     You can download it from CTAN:/macros/latex/contrib/substr/^^J%
9     E.g. one CTAN node is ftp.dante.de.
10    Install substr.sty into your TeX tree.}}
```

At the end of the preamble the package tests whether one of the packages `babel`, `german`, or `ngerman` is loaded. If not it is assumed that American English is wanted (L<sup>A</sup>T<sub>E</sub>X is an American programme). The original date format is saved and the command `\iflanguage` is redefined to process the “true part” for english, american, and USenglish options and otherwise the “false part”.

```

11 \AtBeginDocument{%
12   \@ifpackageloaded{babel}{}{%
13     \@ifpackageloaded{german}{}{%
14       \@ifpackageloaded{ngerman}{}{%
```

Here you can add new languages. Tell me what you have inserted in order to enable me to actualize the package.

```

15     \let\dateamerican\today%
16     \setboolean{isodate@american}{true}%
17     \def\iflanguage#1#2#3{\ifthenelse{%
18       \equal{#1}{english}\or%
19       \equal{#1}{american}\or%
20       \equal{#1}{USenglish}%
21       }{#2}{#3}}%
22   }}}}
```

Declare the boolean variable `isodate@american`. This is necessary because the command `\iflanguage` cannot decide if the language is English or American.

```

23 \newboolean{isodate@american}%
24 % \changes{1.06}{2000/08/08}{Avoid using the hack with redefining
25 % \selectlanguage}
26 % Define the package options.
27 %   \begin{macrocode}
28 \DeclareOption{iso}{\AtBeginDocument{\isodate}}
29 \DeclareOption{num}{\AtBeginDocument{\numdate}}
30 \DeclareOption{short}{\AtBeginDocument{\shortdate}}
31 \DeclareOption{TeX}{\AtBeginDocument{\TeXdate}}
```

```

32 \DeclareOption{orig}{\AtBeginDocument{\origdate}}
33 \ExecuteOptions{orig}
34 \ProcessOptions

Print day or month filled with zero to a format with two digits.
35 \def\dday{\ifthenelse{\number\day<10}{0}{}\number\day}
36 \def\dmmonth{\ifthenelse{\number\month<10}{0}{}\number\month}

Print day and month in numerical format using the right format for the present
language.
37 \DeclareRobustCommand*\num@today}[1]{%
38   \iflanguage{german}{\dday.\,\dmmonth.#1}{%
39     \iflanguage{austrian}{\dday.\,\dmmonth.#1}{%
40       \iflanguage{ngerman}{\dday.\,\dmmonth.#1}{%
41         \iflanguage{naustrian}{\dday.\,\dmmonth.#1}{%

Here you can add new languages. Tell me what you have inserted in order to
enable me to actualize the package.
42     \iflanguage{english}{%
43       \ifthenelse{\boolean{isodate@american}}{%
44         \dmmonth/\dday/}{\dday/\dmmonth/}}{%
45     \dday/\dmmonth/}}}}}%
46 }

```

`\numdate` Switch to long numeric date format.

```

47 \DeclareRobustCommand*\numdate}{%

Find out whether the language may be English or American. The English original
date format does not contain a komma while the american does.
48 \origdate%
49 \setboolean{isodate@american}{false}%
50 \iflanguage{american}{\IfCharInString{,}{\today}{%
51   \setboolean{isodate@american}{true}}}{}}}%

Define the new \today command.
52 \gdef\today{%
53   \num@today{~}%
54   \number\year}}

```

`\shortdate` Switch to short numeric date format.

```

55 \newcounter{yeartwo}
56 \DeclareRobustCommand*\shortdate}{%

Find out whether the language may be English or American. The English original
date format does not contain a komma while the american does.
57 \origdate%
58 \setboolean{isodate@american}{false}%
59 \iflanguage{american}{\IfCharInString{,}{\today}{%
60   \setboolean{isodate@american}{true}}}{}}}%

```

Define the new `\today` command.

```
61 \gdef\today{%
62   \num@today{\,%
63   \setcounter{yeartwo}{\number\year}%
64   \whiledo{\theyeartwo>99}{\setcounter{yeartwo}{\theyeartwo-100}}{-%
65   \ifthenelse{\number\theyeartwo<10}{0}{\theyeartwo}}
```

`\isodate` Switch to ISO date format.

```
66 \DeclareRobustCommand*\isodate}{%
67   \gdef\today{%
68     \number\year\iso@isodash%
69     \ifthenelse{\number\month<10}{0}{\number\month\iso@isodash%
70     \ifthenelse{\number\day<10}{0}{\number\day}}
```

Define the default ISO dash to “-”.

```
71 \def\iso@isodash{-}%
```

`\isodate` Define the command `\isodash` which changes the dash in the ISO date format.

```
72 \DeclareRobustCommand*\isodash}[1]{\def\iso@isodash{#1}}%
```

`\origdate` Switch back to original date format.

```
73 %\DeclareRobustCommand*\origdate}{\gdef\today{\iso@origdate}}
74 \DeclareRobustCommand*\origdate}{\csname date\languagename\endcsname}
```

`\TeXdate` Switch to the T<sub>E</sub>X date format.

```
75 \DeclareRobustCommand*\TeXdate}{%
76   \gdef\today{%
77     \number\year/%
78     \ifthenelse{\number\month<10}{0}{\number\month/%
79     \ifthenelse{\number\day<10}{0}{\number\day}}
```

Print any date (internal command, syntax: `\iso@printdate{yyyy}{mm}{dd}`).

```
80 \DeclareRobustCommand*\iso@printdate}[3]{%
81   \begingroup%
82   \def\year{#1}%
83   \def\month{#2}%
84   \def\day{#3}%
85   \today%
86   \endgroup%
87 }
```

Define counters to count the numbers of special characters in the arguments of the `\printdate` and `\printdateTeX` commands.

```
88 \newcounter{iso@slash}
89 \newcounter{iso@minus}
90 \newcounter{iso@dot}
```

`\printdate` Print any date in the actual date format. This command understands the German, British, and ISO formats.

```
91 \DeclareRobustCommand*\printdate}[1]{%
92 \expandafter\iso@expafterprintdate\expandafter{#1}}%
```

`\iso@expafterprintdate` The command `\iso@expafterprintdate` needs an already expanded argument. So the command `\printdate` expands it and calls `\iso@expafterprintdate`.

The error handling of this macro is very poor. It is just tested if either a “/”, “-”, or “.” is included in the argument twice. It is not tested if the argument consists of numbers, only.

```
93 \DeclareRobustCommand*\iso@expafterprintdate}[1]{%
94 \SubStringsToCounter{iso@slash}{/}{#1}%
95 \SubStringsToCounter{iso@minus}{-}{#1}%
96 \SubStringsToCounter{iso@dot}{.}{#1}%
97 \ifthenelse{\equal{\theiso@dot}{2}}{\printdatenumger{#1}}{%
98 \ifthenelse{\equal{\theiso@minus}{2}}{\printdateiso{#1}}{%
99 \ifthenelse{\equal{\theiso@slash}{2}}{\printdatenumeng{#1}}{%
100 ????\iso@isodash ??\iso@isodash ??%
101 \PackageError{isodate}{unrecognized date format}{Use one of
102 the following formats as macro argument:^^J%
103 \space\space dd.mm.yyyy^^J%
104 \space\space dd/mm/yyyy^^J%
105 \space\space yyyy-mm-dd^^J%
106 Don't use any spaces or commands like \protect\, or
107 \protect~ inside the argument.}%
108 }}}}
```

Analyze the argument containing a date in ISO format and print it. This macro does not contain any error handling.

```
109 \DeclareRobustCommand*\printdateiso}[1]{%
110 \expandafter\iso@printdateiso #1\@empty}
111 \def\iso@printdateiso#1-#2-#3\@empty{\iso@printdate{#1}{#2}{#3}}
```

Analyze the argument containing a date in German numeric format and print it. This macro does not contain any error handling.

```
112 \DeclareRobustCommand*\printdatenumger}[1]{%
113 \expandafter\iso@printdatenumger #1\@empty}
114 \def\iso@printdatenumger#1.#2.#3\@empty{\iso@printdate{#3}{#2}{#1}}
```

Analyze the argument containing a date in British English numeric format and print it. This macro does not contain any error handling.

```
115 \DeclareRobustCommand*\printdatenumeng}[1]{%
116 \expandafter\iso@printdatenumeng #1\@empty}
117 \def\iso@printdatenumeng#1/#2/#3\@empty{\iso@printdate{#3}{#2}{#1}}
```

`\printdateTeX` Analyze the argument containing a date in the LaTeX style yyyy/mm/dd and print it. This format can not be handled automatically by `\printdate` because it could be mixed up with the English format. The error handling of this routine is very poor. It just checks whether the argument contains at least one “/”.

```

118 \DeclareRobustCommand*\printdateTeX[1]{%
119   \expandafter\iso@printdateTeX\expandafter{#1}}
120 \DeclareRobustCommand*\iso@printdateTeX[1]{%
121   \SubStringsToCounter{iso@slash}{/}{#1}%
122   \ifthenelse{\equal{\theiso@slash}{2}}{%
123     {\expandafter\iso@@printdateTeX #1\@empty}{%
124       ????\iso@isodash ??\iso@isodash ??}%
125     \PackageError{isodateo}{unrecognized date format}{Use the format
126       yyyy/mm/dd.^~J%
127       Don't use any spaces or commands like \protect\, or
128       \protect~ inside the argument.}}%
129 }
130 \def\iso@@printdateTeX#1/#2/#3\@empty{\iso@printdate{#1}{#2}{#3}}

```

The end of the package.

## Change History

1.01	General: Improve documentation . . .	1	Throw out the commands <code>\IfSubStringInString</code> and <code>\IfCharInString</code> and use the package <code>substr.sty</code> instead . . . . .	1
1.02	General: Fix American language support by a hack . . . . .	4	<code>\iso@expafterprintdate</code> : Count appearances of “/”, “.”, and “-” and complain if not at least one of them is equal to 2 . . . . .	7
1.03	General: Insert code for handling not loaded language packages . . .	4	<code>\printdateTeX</code> : Count appearances of “/” and complain if not equal to 2 . . . . .	7
1.04	General: Add L <sup>A</sup> T <sub>E</sub> X date format yyyy/mm/dd . . . . .	7	1.06 <code>\numdate</code> : Choose between English and American language . . . . .	5
	Make the commands robust . . .	1	<code>\origdate</code> : Use the command <code>\datelanguage</code> to switch back to the original date format . . .	6
	<code>\TeXdate</code> : Add L <sup>A</sup> T <sub>E</sub> X date format yyyy/mm/dd . . . . .	6	<code>\shortdate</code> : Choose between En- glish and American language . .	5
1.05	General: Change all internal com- mand names to start with <code>\iso@</code> . . . . .	1	1.06a General: Path changed according to new CTAN structure . . . . .	1
	Note that every language that has the same format as English is supported. . . . .	2		

## Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

**Symbols**  
`\@ifpackageloaded` . . . . .

.....	12–14			
<b>A</b>		<b>I</b>		<b>O</b>
<code>\AtBeginDocument</code> ..		<code>\IfCharInString</code> .	50, 59	<code>\numdate</code> .....
.....	11, 28–32	<code>\IfFileExists</code> .....	5	.....
<b>B</b>		<code>\iflanguage</code> .....	17, 38–42, 50, 59	<code>\or</code> .....
<code>\begin</code> .....	27	<code>\ifthenelse</code>	17, 35, 36,	.....
<code>\begingroup</code> .....	81	43, 65, 69, 70,		<code>\origdate</code>
<code>\boolean</code> .....	43	78, 79, 97–99, 122		2, 32, 48, 57, <u>73</u>
<b>C</b>		<code>\iso@printdateTeX</code> .		<b>P</b>
<code>\changes</code> .....	24	.....	123, 130	<code>\PackageError</code>
<code>\csname</code> .....	74	<code>\iso@expafterprintdate</code>	.....	6, 101, 125
<b>D</b>		.....	92, <u>93</u>	<code>\printdate</code> .....
<code>\dateamerican</code> .....	15	<code>\iso@isodash</code> ...	68,	.....
<code>\day</code> .....	35, 70, 79, 84	69, 71, 72, 100, 124		2, <u>91</u>
<code>\dday</code> ..	35, 38–41, 44, 45	<code>\iso@origdate</code> .....	73	<code>\printdateiso</code> ..
<code>\DeclareOption</code> ..	28–32	<code>\iso@printdate</code> .	80,	98, 109
<code>\DeclareRobustCommand</code>		111, 114, 117, 130		<code>\printdatenumeng</code>
.....	37, 47,	<code>\iso@printdateiso</code> .		99, 115
	56, 66, 72–75,	.....	110, 111	<code>\printdatenumger</code>
	80, 91, 93, 109,	<code>\iso@printdatenumeng</code>	.....	97, 112
	112, 115, 118, 120	.....	116, 117	<code>\printdateTeX</code> ...
<code>\dmonth</code>	36, 38–41, 44, 45	<code>\iso@printdatenumger</code>	.....	2, <u>118</u>
<b>E</b>		.....	113, 114	<code>\ProcessOptions</code> ...
<code>\endcsname</code> .....	74	<code>\iso@printdateTeX</code> .		.....
<code>\endgroup</code> .....	86	.....	119, 120	<code>\protect</code> .....
<code>\equal</code>	18–20, 97–99, 122	<code>\isodash</code> .....	2, 72	.....
<code>\ExecuteOptions</code> ...	33	<code>\isodate</code> ..	2, 28, <u>66</u> , <u>72</u>	106, 107, 127, 128
<code>\expandafter</code>	92, 110,	<b>L</b>		<code>\ProvidesPackage</code> ...
	113, 116, 119, 123	<code>\language</code> .....	74	2
<b>F</b>		<b>M</b>		<b>R</b>
<code>\filedate</code> .....	2	<code>\month</code> ...	36, 69, 78, 83	<code>\RequirePackage</code> ...
		<b>N</b>		3–5
		<code>\NeedsTeXFormat</code> .....	1	<b>S</b>
		<code>\newboolean</code> .....	23	<code>\selectlanguage</code> ...
		<code>\num@today</code> ..	37, 53, 62	.....
		<b>Y</b>		25
		<code>\year</code> ..	54, 63, 68, 77, 82	<code>\shortdate</code> ...
				2, 30, <u>55</u>
				<code>\SubStringsToCounter</code>
				.....
				94–96, 121
				<b>T</b>
				<code>\TeXdate</code> .....
				2, 31, <u>75</u>
				<code>\theiso@dot</code> .....
				97
				<code>\theiso@minus</code> .....
				98
				<code>\theiso@slash</code> ..
				99, 122
				<code>\theyeartwo</code> .....
				64, 65
				<code>\today</code>
				1, 15, 50, 52, 59,
				61, 67, 73, 76, 85