

# ConTEXt

**title** : Math Sets  
**subtitle** : ConTEXt port of braket.sty  
**author** : Aditya Mahajan  
**date** : February 25, 2007



## 1 Introduction

I write a lot of probability expressions, which look like

$$E \left\{ \sum_y f(X, y) \middle| Z \right\}$$

The delimiters should scale properly, and so should the *conditional* sign `|`. Moreover the spacing around the conditional sign should be correct. This ensures that the resultant `TEX` code is almost unreadable. In `LATEX` I used to use Donald Arseneau's `braket.sty` to typeset should expressions. `CONTEX` does not have anything similar. So, this is a port of `braket.sty` functionality to `CONTEX`. I have not ported everything, only the features that I use.

## 2 Usage

To use this module add

```
\usemodule[mathsets]
```

on the top of your file. Now, a new *set* can be defined as follows: After which you can use

```
\startformula
  \EXP{f(X) | Y} = \sum_{x} f(x) \PR{x|Y}
\stopformula
```

$$E \{f(X) | Y\} = \sum_x f(x) \Pr(x | Y)$$

We can also run the example specified in `braket.sty` documentation.

```
\definemathset[BRAKET] [left=\langle,right=\rangle]
\definemathset[SET]

\startformula
  \BRAKET{ \phi | \frac{\partial^2}{\partial t^2} \psi }
  \SET{ x \in {\bf R}^2 | 0 < |x| < 5 }
\stopformula
```

$$\left\langle \phi \middle| \frac{\partial^2}{\partial t^2} \middle| \psi \right\rangle \{x \in \mathbf{R}^2 \mid 0 < |x| < 5\}$$

Notice that the `|` protected by `{|}` did not get expanded in the second expression.

## 3 Implementation

```
1 \unprotect
```

Since two letter codes are reserved for system modules, and `CONTEX` seems to be running out of those, I choose a more verbose variable to store options.

```
2 \definesystemvariable {mathset} % Math Set
```

```
\setupmath.. To specify the default values of left, middle, and right delimiters
```

CONTEXT port of brakel.sty

```
3 \def\setupmathset
  {\dosingleargument\getparameters[\??mathset]}

4 \def\definemathset
  {\dodoubleargument\dodefinemathset}

\definemat.. To define new math delimiters

5 \let\currentmathset\empty
  \let\currentmathsetgrouplevel\empty

6 \def\mathsetmiddle
  {\ifnum\currentmathsetgrouplevel=\currentgrouplevel
   \expandafter\firstoftwoarguments
   \else
   \expandafter\secondoftwoarguments
   \fi
  {\egroup\,\middle\mathsetparameter\c!middle\,\bgroup}
  {\mathsetparameter\c!middle}}

7 \def\mathsetparameter#1%
  {\executeifdefined{\??mathset\currentmathset#1}{\executeifdefined{\??mathset#1}\empty}}

8 \def\dodefinemathset[#1][#2]%
  {\getparameters[\??mathset#1][#2]
  \setvalue{#1}{\dododefinemathset[#1]}}
```

Since | is already active, we do not have to make it active again.

```
9 \def\dododefinemathset[#1]#2#%
  {\begingroup
  \def\currentmathset{#1}
  \edef\currentmathsetgrouplevel{\the\numexpr\currentgrouplevel+2\relax}
  \mathcode'\|32768
  \let|\mathsetmiddle
  \def\mathsetarguments{#2}
  \dodododefinemathset}
```

The extra group in the definition of `dodododefinemathset` is so that such expressions turn out correct

$$E \left\{ \left( \frac{a}{b} \right) \middle| \left( \frac{a}{\sum c} \right) \right\}$$

```
10 \def\dodododefinemathset#1%
  {\doifsomething{\mathsetparameter\c!text}
  {\mathop{\mathsetparameter\c!text\mathsetarguments}}
  \left\mathsetparameter\c!left{#1}\right\mathsetparameter\c!right
  \endgroup}

11 \setupmathset
  [ left={\{},
    right={\}},
    middle=\vert]
```

12 \protect

