

ConTEXt

title : ConTEXt User Module
subtitle : Something like KOMA-TypeArea
author : Peter Münster
date : September 12, 2006


```

1 \writestatus{loading}{Something like KOMA-TypeArea}
2 \unprotect
\setupType.. Setting up some values.

```

Default setup:

```
\setupTypeArea[bcor=0pt,oneside=no,alphabets=2.6]
```

Example:

```

\setupTypeArea[bcor=3mm,oneside=yes,alphabets=3.1]
3 \def\setupTypeArea[#1]{\getparameters[T@]{#1}\doTypeArea}

```

Some internal dimensions:

```

4 \newdimen\PageWidth \newdimen\Back
\doifundefined{Width}{\newdimen\Width}
\doifundefined{Height}{\newdimen\Height}

```

This internal macro does the whole work:

```
5 \def\doTypeArea{
```

Set visible page width:

```
6 \PageWidth=\dimexpr\paperwidth-\TA@bcor\relax
```

Determine the paper aspect ratio:

```
7 \edef\Ratio{\withoutpt{\the\dimexpr2\paperheight/(\PageWidth/32768)\relax}}
```

Set the textarea width to X alphabets:

```

8 \setbox\scratchbox\hbox{\dorecurse{26}{\character\recurselevel}}
\Width=\dimexpr\TA@alphabets\wd\scratchbox\relax
\ifdim\Width<\PageWidth\else
\writestatus{error}{line wider than page}\end\fi

```

Set the textarea height proportional to the width:

```
9 \Height=\dimexpr(\Ratio\Width)
```

Set the margin/gutter widths to be equal on a full spread:

```

10 \doifelse\TA@oneside{yes}
{\Back=\dimexpr(\PageWidth - \Width) / 2 + \TA@bcor\relax}
{\Back=\dimexpr(\PageWidth - \Width) / 3 + \TA@bcor\relax}

```

Set the top and bottom margins in a 1:2 ratio, ignoring headers:

```
11 \edef\Top{\the\dimexpr(\paperheight - \Height) / 3 - 3\lineheight\relax}
```

Redefine `\Height` to include header and footer space:

Something like KOMA-TypeArea

```
12 \Height=\dimexpr(\Height + 8\lineheight)

Set up the page layout using the calculated parameters:

13 \setuplayout[
    backspace=\the\Back,
    height=\the\Height,
    width=\the\Width,
    header=2\lineheight,
    headerdistance=\lineheight,
    footer=2\lineheight,
    footerdistance=3\lineheight,
    topspace=\Top]
}

\protect

14 \setupTypeArea[bcor=0pt,oneside=no,alphabets=2.6]

15 \doifnotmode{demo}{\endinput}
```

Usage example:

```
16 \usemodule[typearea]
\setupTypeArea[bcor=0mm,alphabets=3.1]
\setuppagenumbering[alternative=doublesided]
\starttext
\dorecurse4{\framed[width=\textwidth,height=\textheight]{test}\page}
\stoptext
```