

## 0.1 `summary.zelig`: Summary of Simulated Quantities of Interest

### Description

Summarizes the object of class `zelig` (output from `sim`) which contains simulated quantities of interest.

### Usage

```
## S3 method for class 'zelig':  
summary(object, subset = NULL, CI = 95, stats = c("mean", "sd"), ...)
```

### Arguments

<code>object</code>	output object from <code>sim</code> (of class <code>"zelig"</code> ).
<code>subset</code>	takes one of three values: <code>NULL</code> (default) for more than one observation, summarizes all the observations at once for each quantity of interest. a numeric vector indicates which observations to summarize, and summarizes each one independently. <code>all</code> summarizes all the observations independently.
<code>stats</code>	summary statistics to be calculated.
<code>CI</code>	a confidence interval to be calculated.
<code>...</code>	further arguments passed to or from other methods.

### Value

<code>sim</code>	number of simulations, i.e., posterior draws.
<code>x</code>	values of explanatory variables used for simulation.
<code>x1</code>	values of explanatory variables used for simulation of first differences etc.
<code>qi.stats</code>	summary of quantities of interest. Use <code>names</code> to view the model-specific items available in <code>qi.stats</code> .

### Author(s)

Kosuke Imai <kimai@princeton.edu>; Gary King <king@harvard.edu>; Olivia Lau <olau@fas.harvard.edu>

## See Also

`zelig`, `setx`, `sim`, and `names`, and the full Zelig manual at <http://gking.harvard.edu/zelig>.